



CABLE LENGTH	TOLERANCE*				
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER				
STRIP LENGTH	TOLERANCE *				
0-7mm	±0.5mm				
8-29mm	±1.0mm				
30-49mm	±2.0mm				
50-69mm	±3.0mm				
70-100mm	±4.0mm				
OVER 100mm	±5.0mm				
* UNLESS OTHERWISE SPECIFIED					

SOURCE DRAWING - FOR REFERENCE ONLY

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

2. "/S760" DESIGNATES BLACK CABLE JACKET.

NOTES:

3. "/S1057" DESIGNATES GRAY MOLDED PLUG BODIES.

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		rck	3000 CAMPUS MINNEAPOLIS, MN 1-800-544- (763) 553-7 (763) 553-0 www.turck.t	N 55441 7769 '300)708 fax
MATERIAL			DATE 10/18/13	DESCRIPTION PKG 3Z-*-PSG 4/S760/S1		357
	ALL DIMENSIONS DISPLAYED ON THIS	APVD N.M.	SCALE 1=1.0	110 32 130	+/ 3/ 00/ 310	307
	DRAWING ARE FOR REFERENCE ONLY	UNIT OF ME	ASUREMENT	IDENTIFICATION NO.		REV
FINISH	CONTACT TURCK	MILLIMETER [INCH]				R
	FOR MORE INFORMATION					
		DO NOT SCALE THIS DRAWING		FILE: 777032442	SHEET	1 OF 1

В	UPDATED NUMEBR OF CONDUCTORS PER ECO	TV	07/20/16	55677
REV	DESCRIPTION	BY	DATE	ECO NO.