MALE END VIEW	FEMALE END VIEW	WIRING DIAGRAM		SPECIFICATIONS
			CONTACT CARRIER MATERIAL	NYLON OR TPU
4	1		MOLDED HEAD MATERIAL/CO	
	4	4 ←	<u> </u>	BRASS/GOLD
		P1 3 ←		
1 (0 0) 3		2 < N/C	-< 2 COOPLING NOT MATERIAL/PL	
	3 (000) 1	1 < + + + + + + + + + + + + + + + + + +	< 1 RATED CURRENT [A]	4.0 A
			RATED VOLTAGE [V]	250 V
2			< 4 OUTER JACKET MATERIAL/CO	LOR PVC/GREY
2	2		-< 3 J2 CONDUCTOR INSULATION MAT	TERIAL PVC
		N/C	NUMBER OF CONDUCTORS [
	ര ത്വാന്ത		TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)
<u>evro</u> íast.			PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68
38.0 [1 			* METERS (0) SEE NOTE 1 [0.51] \$\$ \$\$ \$\$ \$\$ \$\$ \$\$ \$\$ \$\$ \$\$ \$\$ \$\$ \$\$ \$\$	$\begin{array}{c} & 42.5 \\ \hline & 42.5 \\ \hline & 1.67 \\ \hline & \\ & \\ & \\ & \\ & \\ & \\ & \\ & \\ & \\$
ALL LE STRP L 0-7 8-22 30-4 50-6	WHICHEVER IS GREATER ENGTH TOLERANCE * mm ±0.5mm 9mm ±1.0mm 9mm ±2.0mm 9mm ±3.0mm		20.0 [0.79]	SOURCE DRAWING - FOR REFERENCE ONLY
70-10 OVER 1	00mm ±4.0mm	RELATED DOCUMENTS	3RD ANGLE THIS DRAWING IS PROJECTION CONFIDENTIAL AND THE	3000 CAMPUS DRIVE
	JNLESS OTHERWISE SPECIFIED	1.		MINNEAPOLIS, MN 55441
		2. 3.		(763) 553-7300
NOTES:		4.	WRITTEN PERMISSION IS PROHIBITED.	(763) 553–0708 fa www.turck.us
	U IN NETERO CONTRAT TURCH TO O			
 "*" INDICATES CABLE LENGT SPECIFIC LENGTHS. 	TH IN METERS. CONTACT TURCK TO O	KUEK MOLENCE		01/28/14 DESCRIPTION VB2-FSM 4.4/RK 4T-*/WK 4T-*
SFEUITIU LEINUTHS.		SEE SPECIFICATION	ALL DIMENSIONS APVD C.K. SCALE	1=1.5 VB2-FSM 4.4/RK 41-*/WK 41-* (a) (b)
			DRAWING ARE FOR	
		FINISH		IDENTIFICATION NO. REV
			CONTACT TURCK MILLIMETER [IN	VCH]
UPDATE MALE COUPLING NUT	RDS 04/18	/18 56903 SEE SPECIFICATION	FOR MORE S INFORMATION	
	BY DATE			DRAWING FILE: 7770.32860 SHEET 1 0

DATE

BY

ECO NO.

REV DESCRIPTION

SHEET 1 OF 1

FILE: 777032860

DO NOT SCALE THIS DRAWING