



The M5010 side mount liquid level float switch has a stainless steel stem and float. These switches easily mount into a drilled through-hole for bulkhead mounting. It can be side mounted with the float 90° above or below the through-hole.

Madison Company can also manufacture custom bent stem float switch lengths for your OEM application.

Applications

- Corrosive environments
- Medical
- Food processing
- Heating and Cooling

Material

- Stem and Float: 316 stainless steel

Specifications

- Mounting: 3/8-24 UNF and 1/8" NPT
- Max. temperature: 392°F / 200°C
- Max. pressure: 300 psi
- Switch rating: 30 watt, SPST





| Part Number | Minimum Media SG | Lead Wires | Approvals | Mounting |
|-------------|------------------|--|-------------|-----------|
| M5010 | 0.88 | 24", 22 AWG, Teflon Insulated (standard) | CE, UL, CSA | 3/8-24UNF |
| M5010-18 | 0.88 | 24", 22 AWG, Teflon Insulated (standard) | CE | 1/8" NPT |

Custom Configurations

Contact us directly for custom solutions.
Email: info@madisonco.com

NOTE: Other fittings and voltages are available. [Contact us](#) to discuss your application.



Electrical Considerations

When using Madison level switches, it is important to consider the application's electrical parameters. Our level switches utilize reed switch technology, which are glass encapsulated, magnetically actuated switches. Madison generally provides electrical ratings for resistive loads; however, where the maximum current of the load permits, the switches are capable of controlling devices such as motors, solenoids or coils that produce capacitive or inductive electrical loads. Where possible, Madison recommends the use of general-purpose/isolation relays or controllers to protect the switch.

Protection Techniques and Common Failure Modes

Reed Switch protection is the most successful method of increasing the performance and life of your level sensor. Since every application varies, it is important to understand your protection options. The life of the reed switch is typically 1 million cycles, within rated load conditions. The table below is a guide to suggested protection techniques and common failure modes associated with each load type.

| Load | Load Example | Protection | Diagram | Common Failure Modes | Failure Mode Description |
|--|---|------------------------------|---------|-----------------------------|---|
| Resistive (DC) | Indicator Lamp, Heaters | Current Limiting Resistor | A | In-rush Current (Switching) | In-rush current exceeds rating and welds switch closed |
| | | | | Over-Current (Carry) | Carry-current exceeds rating and switch welds or burns open like a fuse |
| Inductive & Capacitive (DC) | Relay Coil, Solenoids, Motor | Reversing Diode | B | Over-Voltage (Arcing) | Voltage arcing during switching welds contacts closed |
| Inductive & Capacitive (AC or DC) | | Resistor & Capacitor Network | C | | |
| Resistive, Inductive & Capacitive (AC or DC) | Indicator Lamp, Heaters, Relay Coil, Solenoids, Motor | Varistor or MOV | D | Over-Voltage (Arcing) | Transients voltage spikes exceed breakdown voltage and weld switch closed |

Capacitive Load




Diagram A: Current Limiting Resistor

Inductive Load

Inductive Load



Diagram B: Reversing Diode




Diagram C: RC Network




Diagram D: Varistor or MOV

For DC circuits: Insert a 1N4004 diode across the load (i.e.: relay coil) with the cathode end (marked with circular line) connected toward the positive side. This way the diode conducts only when the field collapses. General rule is to use a diode with a voltage rating at least three times the circuit voltage. A 1N4004 has a rating of 1 amp continuous, 30 amp surge, 400V max. Refer to diagram B.

For typical 120V AC circuits: Insert a 50 to 100 ohm, 1/2 watt Resistor in series with a .1 micro farad 400 to 600 volt capacitor across the switch. The capacitor is a high impedance to 60 hertz, but is essentially a short circuit to high frequencies of generated voltages. Alternately, a varistor V130LA10A by itself across the switch will also work for 120V AC. Refer to diagram D.



Madison Company | Sensing Solutions since 1959

27 Business Park Drive
Branford, CT 06405 USA

Toll-Free: 800.466.5383
Outside the USA: +1.203.488.4477

www.madisonsensors.com

