

DIN-Power-Shroud I



Image is for illustration purposes only. Please refer to product description.

Part number	09 06 001 9964
Specification	DIN-Power-Shroud I
HARTING eCatalogue	https://b2b.harting.com/09060019964

Identification

Category	Accessories
Series	DIN 41612
Type of accessory	Pin shroud
Description of the accessory	for screw-fixing of shell housing D20 plastic or D20 metallised. With shroud coding The shroud is assembled onto the Interface connector I and is screw fixed onto the pcb or to the rack.
Features	lead-free

Technical characteristics

Isolation group	IIIa ($175 \leq CTI < 400$)
-----------------	-------------------------------

Material properties

Material (accessories)	Thermoplastic
Colour (accessories)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead



Pushing Performance
Since 1945

Material properties

California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide
California Proposition 65 substances	Lead
California Proposition 65 substances	Nickel
Requirement set with Hazard Levels	R26

Specifications and approvals

Railway classification	F1/I2 acc. to NFF 16-101/102
------------------------	------------------------------

Commercial data

Packaging size	10
Net weight	15.68 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140010659
eCl@ss	27440292 Connector component (accessories)