


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NUMBER	ELEMENT A - AWG [mm]			ELEMENT B - AWG [mm]		PANDUIT COLOR CODE	PANDUIT DIE INDEX NO.	STD. PKG QTY
	COPPER CABLE	GROUND ROD	REBAR	COPPER CABLE				
GCC6X61/0-1/0	#6 SOL - 1/0 STR. [16-50 SQ. mm]	N/A	N/A	#6 SOL - 1/0 STR [16-50 SQ mm]		RED	PG10	1
GCC6X6250-1/0	2 SOL - 250 kcmil [35-120 SQ. mm]	1/2"-5/8" ROD [12.7-15.9 mm]	3/8"-1/2"; #3-#4 REBAR [9.5-12.7mm; #10M-#13M REBAR]	#6 SOL - 1/0 STR [16-50 SQ mm]		BLACK	PG25	1
GCC6X6250-250	2 SOL - 250 kcmil [35-120 SQ. mm]	1/2"-5/8" ROD [12.7-15.9 mm]	3/8"-1/2"; #3-#4 REBAR [9.5-12.7mm; #10M-#13M REBAR]	2 SOL - 250 kcmil [35-120 SQ mm]		BLACK	PG25	1
GCC6X6500-1/0	250 - 500 kcmil [150-240 SQ. mm]	1/2"-3/4" ROD [12.7-19.1 mm]	5/8"-3/4"; #5-#6 REBAR [15.9-19.1mm; #16M-#19M REBAR]	#6 SOL - 1/0 STR [16-50 SQ mm]		BLUE	PG50	1
GCC6X6500-250	250 - 500 kcmil [150-240 SQ. mm]	1/2"-3/4" ROD [12.7-19.1 mm]	5/8"-3/4"; #5-#6 REBAR [15.9-19.1mm; #16M-#19M REBAR]	2 SOL - 250 kcmil [35-120 SQ mm]		BLUE	PG50	1



NOTES

- DIMENSIONS IN PARENTHESIS ARE MILLIMETERS.
- UL 467 LISTED AND CSA 22.2 CERTIFIED FOR GROUNDING & BONDING SUITABLE FOR DIRECT BURIAL IN EARTH OR CONCRETE WHEN CRIMPED WITH PANDUIT OR INDUSTRY STANDARD CRIMPING TOOLS & PANDUIT DIES.
- ENHANCED CRIMP PROCESS WITH PATENTED TECHNOLOGY MEETS IEEE STD 837 - 2002 AND REV 2014. SEE INSTRUCTION SHEET T-PMPI-289-PC ON WWW.PANDUIT.COM FOR FURTHER DETAILS.
- PRE-APPLIED ANTIOXIDANT COMPOUND ENSURES A HIGH QUALITY MECHANICAL AND ELECTRICAL BOND, SPEEDING INSTALLATION.
- CABLE TIES ARE PROVIDED WITH THE TAPS TO RETAIN WIRES IN POSITION DURING CRIMPING.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
03	12/21	JHNU	JADE	JADE	REVISED NOTE 3 TO REFERENCE INSTRUCTION SHEET REVISED TITLE BLOCK	114242
02	12/10	JHNU	RGB	RGB	ADDED AGENCY LOGOS	N41749BC-C41749
01	3/09	JHNU	RGB	RGB	REV'D MARKING ON ELEMENT A OF GCC6X6250-1/0, ELEMENT B OF GCC6X6250-250, ELEMENT A OF GCC6X6500-1/0, ELEMENT A OF GCC6X6500-250 TO SHOW REBAR INFO REMOVED * NOTE	
00	4/08	JHNU	RGB	RGB	DRAWING RELEASED	

TITLE						
6X6 GROUNDING CONNECTORS						
CUSTOMER DRAWING						
ITEM REVISION NAME			N41749BC/03			
DATASET FILE NAME			C41749/03.SLDDRW			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]						
.X ±		.XXX ± .005		ANGLES ± 1°		
.XX ± .03						
DRAWN BY			DATE		CHK	
JHNU			4/08		RGB	
SCALE			N/A			
DRAWING NUMBER						C41749
SHEET 1 OF 1						SIZE B