

FEATURES

- Fits standard rectangular cutout.
- Various hole mounting options.
- No soldering or punch termination. Use standard cable for each connector style.
- Low rear profile.

RS PRO Cat6 RJ45 Feedthrough Connectors

RS Stock No.: 2576705, 2576706



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Ethernet Connectors

Product Description

Cat6 RJ45 Right angle feedthrough connector. A feedthrough, data connector for electrical instrumentation. Used for developing custom I/O configurations for wall plates, rack panels, etc.

Common cabling can be used for front and rear connections. No soldering and no punch terminations - just use the standard cable for that particular connector style.

A low rear profile accommodates the tightest behind-the-panel spaces.

Please note: Functionality is affected by cable quality, length and cable wiring configuration.

General Specifications

Gender	Female
LAN Category	Cat 6
Number of Ways	8P8C
Number of Ports	1
Shielded	Yes
Contact Material	Phosphor Bronze
Contact Plating	Gold plating
Body Orientation	Straight
Termination Method	Feed through
Housing Material	RJ45 In-Line Coupler: ABS UL94-V2 PCB: FR4 Frame: Diecast, Nickel or Black plated
Frame Colour	Metal
Maximum Operating Temperature	Max +60°C
Minimum Operating Temperature	Min -10°C

Electrical Specifications

Current Rating	1.5A RMS
Voltage Rating	125VAC

Mechanical Specifications

Mounting Hole	CSK hole
Frame Style	Metal Slim type

Approvals

Compliance/Certifications	REACH, RoHS
Standards Met	T568A & T568B wiring. Meets ISO/IEC 11801 and EN50173 Meets ANSI/TIA/EIA 568B.2

Similar Products

Parameters	2576706
Brand	RS PRO
Gender	Female
LAN Category	Cat 6
Number of Ways	8P8C
Number of Ports	1
Shielded	Yes
Contact Material	Phosphor Bronze
Contact Plating	Gold plating
Body Orientation	Straight
Termination Method	Feed through
Frame Colour	Black
Maximum Operating Temperature	Max +60°C
Minimum Operating Temperature	Min -10°C
Current Rating	1.5A RMS
Voltage Rating	125VAC
Mounting Hole	CSK

