6-2368393-3 <

AMP | LEAVYSEAL TE Internal #: 6-2368393-3 Receptacle, Wire-to-Wire, 39 Position, .21 in [5.5 mm] Centerline, Sealable, Brown, Power & Signal, Cable Mount (Free-Hanging), LEAVYSEAL

View on TE.com >

Connectors > Automotive Connectors > Automotive Housings > LEAVYSEAL Housings



Connector System: Wire-to-Wire

Number of Positions: 39

Connector & Housing Type: Receptacle

Centerline (Pitch): 5.5 mm [.21 in]

Sealable: Yes

All LEAVYSEAL Housings (64)



Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Receptacle
Sealable	Yes
Primary Locking Feature	Contact Retainer
Configuration Features	
Blank Cavity Position	0
Number of Positions	39
Number of Rows	3
Electrical Characteristics	
Operating Voltage	36 VDC

Receptacle, Wire-to-Wire, 39 Position, .21 in [5.5 mm] Centerline, Sealable, Brown, Power & Signal, Cable Mount (Free-Hanging), LEAVYSEAL



Body Features

Cable Exit Angle	90°
Primary Product Color	Brown
Connector & Keying Code	F
Contact Features	
Contact Size	2.8mm
Mating Tab Width	2.8 mm[.11 in]
Contact Current Rating (Max)	25 A
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	5.5 mm[.21 in]
Dimensions	
Connector Height	45.93 mm
Product Width	47.1 mm
Product Length	125 mm
Row-to-Row Spacing	5 mm
Compatible Insulation Diameter Range	2.2 – 3 mm
Usage Conditions	
Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Degree of Protection	IP67, IP69K
Agency/Standard	LV214
Packaging Features	
Packaging Quantity	44
Packaging Method	Standard

C For support call+1 800 522 6752

Receptacle, Wire-to-Wire, 39 Position, .21 in [5.5 mm] Centerline, Sealable, Brown, Power & Signal, Cable Mount (Free-Hanging), LEAVYSEAL



Other

Serviceable	Yes	
Product Compliance For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC	
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.	
Solder Process Capability	Not reviewed for solder process capability	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent

chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Also in the Series | LEAVYSEAL

C For support call+1 800 522 6752

Receptacle, Wire-to-Wire, 39 Position, .21 in [5.5 mm] Centerline, Sealable, Brown, Power & Signal, Cable Mount (Free-Hanging), LEAVYSEAL







Customers Also Bought



TE Part #788189-2 CPC 17-3 RCPT ASY,REV SEX	TE Part #2-330648-1 PIDG 22-16 22-18 MIL R 4; TAPE	TE Part #2177090-3 STEEL,OUTER FERRULE,8MM HV, 25SQMM	TE Part #1-1633961-2 CRIMPER, INSULATION F PREMIUM
ETE	E TE	E TE	
TE Part #1587940-3 CABLE SEAL RETAINER, SIZE C	TE Part #2103013-3 CABLE SEAL RETAINER, SIZE 2, OR, HVA280	TE Part #2208669-3 8MM HV, CONTACT,ASSY	TE Part #4-1633932-0 ANVIL, COMBINATION



Documents

Receptacle, Wire-to-Wire, 39 Position, .21 in [5.5 mm] Centerline, Sealable, Brown, Power & Signal, Cable Mount (Free-Hanging), LEAVYSEAL



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6-2368393-3_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6-2368393-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6-2368393-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

German