

# **Emergency Fallback Ventilation System for SRCOOL3KTP Air Conditioner**

# MODEL NUMBER: SRCOOLTMVENT











Vents hot air out of your rack enclosure through convection if the air conditioner stops cooling due to power failure.

#### **Features**

#### Allows Hot Air Trapped Inside a Rack Enclosure to Vent Out During Power Emergencies

This SmartRack® emergency fallback ventilation system works in conjunction with the SRCOOL3KTP Top-of-Rack Precision Cooling Air Conditioner (sold separately) to help prevent rack equipment from overheating in case of a cooling system failure. If the SRCOOL3KTP malfunctions due to power failure, the SRCOOLTMVENT's embedded thermal sensor triggers a lid release, allowing the hot air within the rack to dissipate. An SNMP alert via the SRCOOL3KTP's remote management will notify you that the vent has opened.

#### Easy to Install with Included Hardware

The SRCOOLTMVENT inserts easily into the SRCOOL3KTP's reserved slot using the included mounting screws and can be retrofitted into existing installations. A 12V DC power supply is also included.

# Specifications

| OVERVIEW                                  |                          |  |
|---|--------------------------|--|
| UPC Code                                  | 037332267238             |  |
| Accessory Type                            | Duct Kit                 |  |
| Accessory Class                           | Cooling Accessories      |  |
|   |                          |  |
| INPUT                                     |                          |  |
| AC Power Adapter Plug(s)                  | NEMA 1-15P North America |  |
| AC Power Adapter Input Specs (V / Hz / A) | 100-240V, 50/60 Hz, 1A   |  |

## **Highlights**

- Performs in conjunction with the SRCOOL3KTP top-of-rack air conditioner
- Keeps rack equipment safely functioning in case of temporary cooling loss
- Integrates with SRCOOL3KTP's remote management with no special configurations
- Easy to install with included hardware and external power supply

# **System Requirements**

Requires installation with SRCOOL3KTP air conditioner

### **Package Includes**

- · Emergency vent assembly
- (6) Mounting screws
- External power supply (Input: 100–240V, 50/60 Hz, 1A; Output: 12V 2.5A)
- Installation instructions



| AC Power Adapter Output Specs (V / A) | 12V 2.5A  |
|---------------------------------------|---|
| AC Power Adapter Cord Length (ft.)    | 6   |
| POWER                                 |   |
| POWER                                 |   |
| Power Source Type                     | AC Adapter  |
| PHYSICAL                              |   |
| Material of Construction              | Steel housing   |
| Housing Color                         | Black   |
| Unit Dimensions (hwd / in.)           | 3.440 x 22.320 x 11.850   |
| Unit Dimensions (hwd / cm)            | 8.74 x 56.59 x 30.1   |
| Unit Weight (lbs.)                    | 17.2  |
| Unit Weight (kg)                      | 7.80  |
| Mounting Details                      | Allows heat from the rack to escape through the SRCOOL3KTP by opening up the top of the cooler. |
| STANDARDS & COMPLIANCE                |   |
| STANDARDS & COMPLIANCE                |   |
| External Power Supply Certifications  | UL  |
| Product Compliance                    | RoHS  |
| WARDANITY & CURRORT                   |   |
| WARRANTY & SUPPORT                    |   |
| Product Warranty Period (Worldwide)   | 5-year limited warranty   |
|                                       |   |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.