

8-Port Metal DIN-Rail Mounting Keystone Patch Panel with Grounding, Black/Silver, TAA

MODEL NUMBER: N063-008-ENC



Accepts snap-in keystone jacks and couplers to help you manage your DIN-rail network cable application.

Features

Organizes a Wide Variety of Ethernet Network Patch Cables in Your DIN-Rail Installation

This DIN-rail mounting patch panel lets you manage network cable interconnectivity with eight blank cutouts, which accommodate all snap-in keystone jacks and in-line couplers. Each RJ45 Ethernet cutout features metal contacts for grounding purposes. The N063-008-ENC also allows patching with NGI/NFI DIN-rail-mount Ethernet switches (sold separately).

Easy to Install in Rugged Industrial Applications

Made from sheet metal with a plastic rear frame, the N063-008-ENC quickly installs on a standard 35-millimeter DIN rail. Ports are numbered to help you organize your application and identify specific connections. A grounding wire is included.

TAA-Compliant for GSA Schedule Purchases

The N063-008-ENC is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Specifications

OVERVIEW	
UPC Code	037332276933
Technology	Cat5/5e; Cat6; Cat6a
Firmware / Software Docs	
Offset Ports	No
PHYSICAL	

Highlights

- Rugged metal front construction with plastic rear frame for industrial applications
- 8 front blank cutouts compatible with all keystone jacks and couplers
- Numbered ports allow at-a-glance identification of cable connections
- Built-in mounting clip attaches easily to standard 35 mm DIN rail with no tools needed
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

- N063-008-ENC Metal DIN-Rail Mounting Keystone Patch Panel, 8 Ports
- Grounding wire
- Installation instructions

Primary Form Factor	DIN-Rail
Color	Black; Silver
Material of Construction	Plastic (PC FR) & Metal (SPCC/FE)
Total Number of Ports	8
Shipping Dimensions (hwd / in.)	2.40 x 3.20 x 8.00
Shipping Weight (lbs.)	0.51
Unit Dimensions (hwd / in.)	6.060 x 2.190 x 3.100
ENVIRONMENTAL	
Operating Temperature Range	-13° to 122°F (-25° to 50°C)
Storage Temperature Range	-40° to 158°F (-40° to 70°C)
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	10% to 85% RH, (Non-Condensing)
CONNECTIONS	
Number of Ports	8
Side A - Connector 1	(8) KEYSTONE JACK CUTOUT
FEATURES & SPECIFICATIONS	
All-in-One Kit	No
Antibacterial	No
IP68 Rated	No
IP20 Rated	No
Numbered Ports	Yes
DIN Mountable	Yes
Keystone Jacks	Yes
Built-in Cables	No
Color-Coded Connections	No
EIA/TIA 2/32 Spacing	No
Labeled Ports	No
Down-Angled Ports	No
Panel Applications	Ethernet
STANDARDS & COMPLIANCE	
Product Compliance	CE (Europe); REACH; RoHS; UKCA; Trade Agreements Act (TAA)
WARRANTY & SUPPORT	



1000 Eaton Boulevard
Cleveland, OH 44122
United States

Product Warranty Period (Worldwide)	Lifetime limited warranty
--	---------------------------



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.