



Main

Range	TeSys
Product name	TeSys Ultra
Device short name	LUB
Product or Component Type	Non reversing power base
Device Application	Motor control Motor protection
Poles description	3P
Suitability for isolation	Yes
[Ue] rated operational voltage	690 V AC power circuit
Network frequency	40...60 Hz
[I _{th}] conventional free air thermal current	32 A
[I _e] rated operational current	28.5 A ≤ 440 V 23 A 500 V 21 A 690 V
Utilisation category	AC-43 AC-44 AC-41
[I _{cs}] rated service breaking capacity	50 KA 230 V 50 KA 440 V 10 KA 500 V 4 kA 690 V
Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts type	Linked contacts 1 NO + 1 NC) IEC 60947-4-1 Mirror contact 1 NC) IEC 60947-1
[U _c] control circuit voltage	24 V AC 50/60 Hz 24 V DC 48...72 V AC 50/60 Hz 48...72 V DC 110...240 V AC 50/60 Hz 110...220 V DC

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Typical current consumption	<p>200 MA 24 V DC I maximum while closing with LUCM</p> <p>220 MA 24 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>220 MA 24 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>25 MA 110...220 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>25 MA 110...240 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>280 MA 110...220 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 MA 110...240 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 MA 48...72 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 MA 48...72 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>45 MA 48...72 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>45 MA 48...72 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>75 MA 24 V DC I rms sealed with LUCM</p> <p>80 MA 24 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>90 mA 24 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p>
Heat dissipation	<p>3 W control circuit with LUCA, LUCB, LUCC, LUCD</p> <p>1.8 W control circuit with LUCM</p>
Safety reliability level	<p>B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1</p> <p>B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1</p>
Operating time	<p>35 ms opening with LUCA, LUCB, LUCC, LUCD, LUCM control circuit</p> <p>50 ms \geq 72 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>60 ms 48 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>70 ms 24 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>65 ms closing with LUCM control circuit</p>
Mechanical durability	15 Mcycles
Maximum operating rate	3600 cyc/h
Product Certifications	<p>CE</p> <p>UL</p> <p>CSA</p> <p>CCC</p> <p>EAC</p> <p>ASEFA</p> <p>ATEX</p> <p>Marine</p>
Standards	<p>EN 60947-6-2</p> <p>IEC 60947-6-2</p> <p>UL 60947-4-1, with phase barrier</p> <p>CSA C22.2 No 60947-4-1, with phase barrier</p>
[Ui] rated insulation voltage	<p>690 V IEC 60947-6-2 3)</p> <p>600 V UL 60947-4-1</p> <p>600 V CSA C22.2 No 60947-4-1</p>
[Uimp] rated impulse withstand voltage	6 kVIEC 60947-6-2
Safe separation of circuit	<p>400 V SELV between the control and auxiliary circuits IEC 60947-1 appendix N</p> <p>400 V SELV between the control or auxiliary circuit and the main circuit IEC 60947-1 appendix N</p>
Fixing mode	<p>Clipped DIN rail)</p> <p>Screw-fixed plate)</p>
Connections - terminals	<p>Control circuit screw clamp terminals 1 0.00...0.00 in² (0.34...1.5 mm²) flexible with cable end</p> <p>Control circuit screw clamp terminals 1 0.00...0.00 in² (0.75...1.5 mm²) flexible without cable end</p> <p>Control circuit screw clamp terminals 1 0.00...0.00 in² (0.75...1.5 mm²) rigid</p> <p>Control circuit screw clamp terminals 2 0.00...0.00 in² (0.34...1.5 mm²) flexible with cable end</p> <p>Control circuit screw clamp terminals 2 0.00...0.00 in² (0.75...1.5 mm²) flexible without cable end</p> <p>Control circuit screw clamp terminals 2 0.00...0.00 in² (0.75...1.5 mm²) rigid</p> <p>Power circuit screw clamp terminals 1 0.00...0.02 in² (1...10 mm²) rigid</p> <p>Power circuit screw clamp terminals 1 0.00...0.01 in² (1...6 mm²) flexible with cable end</p> <p>Power circuit screw clamp terminals 1 0.00...0.02 in² (2.5...10 mm²) flexible without cable end</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in² (1...6 mm²) flexible with cable end</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in² (1...6 mm²) rigid</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in² (1.5...6 mm²) flexible without cable end</p>

Tightening torque	Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) flat 0.20 in (5 mm) Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) Philips no 1 0.20 in (5 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) flat 0.24 in (6 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) Philips No 2 0.24 in (6 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) pozidriv No 2 0.24 in (6 mm)
Width	1.77 in (45 mm)
Height	6.06 in (154 mm)
Depth	4.96 in (126 mm)
Product Weight	1.98 lb(US) (0.9 kg)
Compatibility code	LUB

Environment

IP degree of protection	IP20 IEC 60947-1 front panel and wired terminals) IP20 IEC 60947-1 other faces) IP40 IEC 60947-1 front panel outside connection zone)
Protective treatment	TH IEC 60068
Ambient air temperature for operation	-13...140 °F (-25...60 °C) with LUCM -13...158 °F (-25...70 °C) with LUCA, LUCB, LUCC, LUCD
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Fire resistance	1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12
Operating altitude	6561.68 ft (2000 m)
Shock resistance	10 gn power poles open IEC 60068-2-27 15 gn power poles closed IEC 60068-2-27
Vibration resistance	2 gn 5...300 Hz) power poles open IEC 60068-2-27 4 gn 5...300 Hz) power poles closed IEC 60068-2-27
Resistance to electrostatic discharge	8 KV 3 in open air IEC 61000-4-2 8 kV 4 on contact IEC 61000-4-2
Resistance to radiated fields	9.14 V/m (10 V/m) 3 IEC 61000-4-3
Resistance to fast transients	2 KV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
Non-dissipating shock wave	1 KV serial mode 24...240 V AC IEC 60947-6-2 1 KV serial mode 48...220 V DC IEC 60947-6-2 2 KV common mode 24...240 V AC IEC 60947-6-2 2 kV common mode 48...220 V DC IEC 60947-6-2
Immunity to radioelectric fields	10 V IEC 61000-4-6
Immunity to microbreaks	3 ms control circuit
Immunity to voltage dips	70 % / 500 ms IEC 61000-4-11

Ordering and shipping details

Category	22396-TESYS U - SELF PRCTD STARTER (LUB)
Discount Schedule	I11
GTIN	3389110362787
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.17 in (5.500 cm)
Package 1 Width	5.43 in (13.800 cm)
Package 1 Length	6.65 in (16.900 cm)
Package 1 Weight	29.88 oz (847.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	19.27 lb(US) (8.740 kg)
Unit Type of Package 3	P06

Number of Units in Package 3	160
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	325.93 lb(US) (147.840 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes