

9978 Hook-up/Lead - UL AWM Style 1061



Description:

Tinned copper conductor, semi-rigid PVC insulation (solid conductors suitable for wire wrap applications).

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	30
Stranding	Solid
Conductor Material	TC - Tinned Copper
INSULATION:	
Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.010 in.
OVERALL:	
Overall Nominal Diameter	.030 in.
APPLICABLE SPECIFICATIONS AND AGENCY	Y COMPLIANCE:
APPLICABLE STANDARDS:	
UL AWM Style	1061
UL Rating	300 V RMS, 80°C
CSA Type	AWM I, A/B
CSA Rating	300 V RMS, 80°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
FLAME TEST:	
UL Flame Test	VW-1
PLENUM/NON-PLENUM:	
Plenum (Y/N)	Ν

PUT-UPS AND COLORS:



9978 Hook-up/Lead - UL AWM Style 1061

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9978 001100	30 SOL PVC BRN	100	0.1	BROWN	
9978 002100	30 SOL PVC RED	100	0.1	RED	
9978 0021000	30 SOL PVC RED	1000	1	RED	
9978 003100	30 SOL PVC ORG	100	0.1	ORANGE	
9978 0031000	30 SOL PVC ORG	1000	1	ORANGE	
9978 004100	30 SOL PVC YEL	100	0.1	YELLOW	
9978 0041000	30 SOL PVC YEL	1000	1	YELLOW	
9978 005100	30 SOL PVC GRN	100	0.1	GREEN, DARK	
9978 0051000	30 SOL PVC GRN	1000	1	GREEN, DARK	
9978 007100	30 SOL PVC VIO	100	0.1	VIOLET	
9978 0071000	30 SOL PVC VIO	1000	1	VIOLET	
9978 008100	30 SOL PVC GRY	100	0.1	GRAY	
9978 009100	30 SOL PVC WHT	100	0.1	WHITE	
9978 0091000	30 SOL PVC WHT	1000	1	WHITE	
9978 010100	30 SOL PVC BLK	100	0.1	BLACK	
9978 0101000	30 SOL PVC BLK	1000	1	BLACK	
9978 013100	30 SOL PVC D. BLU	100	0.1	BLUE, DARK	
9978 0131000	30 SOL PVC D. BLU	1000	1	BLUE, DARK	

Revision Number: 1

Revision Date: 11-17-2006

Detailed Specifications & Technical Data



9978 Hook-up/Lead - UL AWM Style 1061

© Copyright 2006 Belden, Inc All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & California Proposition 65 Consent Judgment For Wire & California Proposition 65 Consent Judgment 2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.