

8899 Hook-up/Lead - Test Prod Wire

		See Put-ups and Colors
escription:		
inned copper conductor, rubber insulated.		
HYSICAL CHARACTERISTICS:		
CONDUCTOR:		
umber of Conductors	1	
otal Number of Conductors	1	
WG	18	
randing	65x36	
onductor Material	TC - Tinned Copper	
NSULATION:		
sulation Material	Rubber	
sulation Thickness	.045 in.	
VERALL:		
verall Nominal Diameter	.144 in.	
IECHANICAL CHARACTERISTICS:		
on-UL Temperature Rating	90°C	
PPLICABLE SPECIFICATIONS AND AGENC	Y COMPLIANCE:	
PPLICABLE STANDARDS:		
U CE Mark (Y/N)	Yes	
U RoHS Compliant (Y/N)	Yes	
U RoHS Compliance Date (mm/dd/yyyy):	01/01/2004	
LENUM/NON-PLENUM:		
enum (Y/N)	Ν	
LECTRICAL CHARACTERISTICS:		
iggested Working Voltage	5000 V	
reakdown Voltage	20000 V	

## **PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes	



8899	Hook-up/Lead	-	Test Prod Wire	è
------	--------------	---	----------------	---

8899 00210	#18 STR EPDM RED	10	0.18	RED	
8899 002100	#18 STR EPDM RED	100	2.2	RED	
8899 0021000	#18 STR EPDM RED	1000	15	RED	С
8899 00225	#18 STR EPDM RED	25	0.6	RED	
8899 002500	#18 STR EPDM RED	500	8.5	RED	
8899 002U1000	18 STR EPDM RED	U1000	16	RED	
8899 002U500	18 STR EPDM RED	U500	8.5	RED	
8899 004100	#18 STR EPDM YEL	100	2.2	YELLOW	
8899 00425	#18 STR EPDM YEL	25	0.575	YELLOW	
8899 004500	#18 STR EPDM YEL	500	8	YELLOW	
8899 005100	#18 STR EPDM DGRN	100	2.2	GREEN, DARK	
8899 00525	#18 STR EPDM DGRN	25	0.6	GREEN, DARK	
8899 005500	#18 STR EPDM DGRN	500	8.5	GREEN, DARK	
8899 006100	#18 STR EPDM LBLU	100	2.2	BLUE, LIGHT	
8899 00625	#18 STR EPDM LBLU	25	0.6	BLUE, LIGHT	
8899 006500	#18 STR EPDM LBLU	500	8.5	BLUE, LIGHT	
8899 008100	#18 STR EPDM GRY	100	2.2	GRAY	
8899 00825	#18 STR EPDM GRY	25	0.575	GRAY	
8899 008500	#18 STR EPDM GRY	500	8	GRAY	
8899 009100	#18 STR EPDM WHT	100	2.3	WHITE	
8899 00925	#18 STR EPDM WHT	25	0.6	WHITE	
8899 009500	#18 STR EPDM WHT	500	8.5	WHITE	
8899 01010	#18 STR EPDM BLK	10	0.18	BLACK	
8899 010100	18 STR EPDM BLK	100	2.3	BLACK	
8899 0101000	#18 STR EPDM BLK	1000	15	BLACK	С
8899 01025	18 STR EPDM BLK	25	0.6	BLACK	
8899 010500	#18 STR EPDM BLK	500	8.5	BLACK	
8899 010U1000	#18 STR EPDM BLK	U1000	16	BLACK	



## 8899 Hook-up/Lead - Test Prod Wire

8899 010U500	18 STR EPDM BLK	U500	8.5	BLACK	
8899 06114	#18 STR EPDM BLK & RED	14	0.448	BLACK & RED	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-02-2005

© Copyright 2006 Belden, Inc

All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & amp; Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.