

U9VL-FP



System: Lithium-Manganese Dioxide Non-Rechargeable

Part No: U9VL-FP

✓ RoHS Exempt ([see position statement](#))

Specifications

NSN:	6135-01-369-9792
Volt Range:	5.4 to 9.9 V
Average Voltage:	9.0 V
Nominal Capacity:	1.2 Ah @ 9 mA to 5.4 V @ 23° C
Max. Discharge:	120 mA continuous
Pulse Capacity:	Up to 400 mA Varies according to pulse characteristics, temperature, cell history, and the application. Consult Ultralife.
Weight:	33.8 Grams
Operating Temp.:	-20° C to 60° C
Storage Temp.:	-40° C to 60° C
Self Discharge:	< 0.16 % per Month
Exterior/Housing:	Plastic / Foil Label
Terminals/Connector:	Ni-plated Miniature Snap
Safety:	Recognized under the Component Program of Underwriters Laboratories, Inc. Material Safety Datasheet - MSDS001.
Transportation:	Excepted from Regulations - see note 1
Note 1:	For a complete description of transportation regulations and definitions of the transportation classifications "Excepted" and "Class 9," refer to the Ultralife web site at www.ultralifebatteries.com .
Note 2:	NEDA number is 1604 LC
Note 3:	100 count. Call for other variations. Sold only in foil packs as U9VL-FP.

Product Drawings

