



Brilliance by design

SloanLED™

# Panel Mount LED Indicator Models 150 & 240


www.SloanLED.com

## MODEL 150

The 150 Model incorporates a non-relampable diffused LED in a choice of colors. For panel mounting through a 5/32" (0.156") dia. hole; snap fits, needs no mounting hardware. No lens for maximum viewing angle. Supplied with 6" wire leads. Can be supplied with or without built in current limiting resistor.



Suggested mounting diameter 5/32"



### FEATURES

- Snap mounts in 5/32" (0.156") diameter hole, with mounting clip
- Supplied with 6" wire leads
- 26 AWG Stranded Cu
- Uses T-1 LED
- For operation from 5V., 12V., 24V. or 28V. sources, with built-in resistor
- No lens for maximum viewing angle
- Fits 1/8" panel thickness

## HOW TO ORDER

For model no. 150-2X colors available are Red, Green, Yellow and Amber.

Where the 'X' appears insert:

1-Red	5-Ultra Green
2-Green	6-Ultra Blue
3-Yellow	7-Pure White
4-Amber	

Voltage	Model No.
2vdc*	150-2X
5vdc	150-5X
12vdc	150-12X
24vdc	150-24X
28vdc	150-28X

\*external resistor required


150 240

## MODEL 240

The 240 Model incorporates a non-relampable diffused LED in a choice of colors. For panel mounting through a 1/4" (0.250") dia. hole; snap fits, needs no mounting hardware. No lens for maximum viewing angle. Supplied with 6" wire leads. Can be supplied without built in current limiting resistor.



Suggested mounting diameter 1/4"



### FEATURES

- Snap mounts in 1/4" (0.250") diameter hole; needs no mounting hardware
- Supplied with 6" wire leads
- 26 AWG Stranded Cu
- No lens for maximum viewing angle
- Uses T-1 3/4 LED
- Fits 1/8" panel thickness

NOTE:

\* For Voltage/Current Specs, see page A-1.  
LEDs continuous forward current = 20 mA  
Omit voltage/current specification to order without built-in resistor.

## HOW TO ORDER

Voltage	Model No.	Where the 'X' appears insert:
*external resistor required	240-2X	1-Red 6-Ultra Blue
2vcd*	240-5X	2-Green 7-Pure White
5vcd	240-12X	3-Yellow
12vcd	240-24X	4-Amber
24vcd	240-28X	5-Ultra Green
28vcd		

3-1