

Conventional and Addressable Accessories

Relays

PAM Series



The PAM1 Relay is an encapsulated multi-voltage device providing 10 Amp Form C contacts. The relay may be energized by one of three input voltages: 24V AC, 24V DC, or 115V AC. A red light emitting diode (LED) that indicates the relay coil is energized.

The PAM1 may be mounted by using the double-sided adhesive tape, the self-drilling screw, or loosely placed in a back box.

The PAM1 is suitable for applications where remote relays are required for control or status feedback, such as HVAC, temperature control, fire alarm, security, energy management and lighting control systems.

Features and Specifications

- Completely encapsulated 10 Amp relay
- Relay may be energized by one of three input voltages
- Red LED illuminates when relay coil is energized
- May be mounted by double-sided adhesive tape, self-drilling screw or placed in back box
- 6 in (150mm) wire leads for electrical connections
- Operating temperature range: 32°F to 120°F (0°C to 49°C)

Ordering Information

Description	Cat. No.	Operating Voltage	Current	Contacts	Contact Rating
Control Relay	PAM1	24V AC, 24V DC, 115V AC	0.015 A	SPDT	10 A @ 115V AC

Weights and Dimensions

Cat. No.	Approx. Shipping Weight (lb.)	Dimensions ¹		
		Height (in.)	Width (in.)	Depth (in.)
PAM1	0.8	1.5 (38.1mm)	1 (24.5mm)	0.875 (22.2mm)

¹With 6" (150mm) wire leads, 18 AWG (1.00mm²)

