

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 51014

DESCRIPTION: 12 AWG STRANDED TYPE THHN/THWN INSULATED WIRE

CONSTRUCTION: This cable consists of one bare copper conductor with integral insulation and jacket.

APPROVALS: UL Standard 83 and Subject 758

APPLICATION: Insulated Wire, Appliance Wiring Material, Canada T90-Nylon, Canada TWN75

Construction	Parameters:
--------------	-------------

Conductor 12 AWG Bare Copper

Stranding 19/.0185"
Insulation Material PVC/Nylon
Insulation Thickness 0.016" Nom.
Nylon Insulation Thickness 0.005" Nom.
Insulated Conductor Diameter 0.131" Nom.
Approximate Cable Weight 24.7 Lbs/1M' Nom.

Electrical & Environmental Properties:

Temperature Rating -20°C to 105°C
Operating Voltage 600 V RMS Max.
DC Resistance per Conductor @ 20°C 1.58 Ohms/1M' Nom.

Insulation/Jacket Color Varies (Consult factory for availability)

Legend (Surface Ink Print)

CCI TRIANGLE 12 AWG (3.31mm2) THHN OR THWN E101736 (UL) 600V OR

AWM STYLE 1316 & 1408 & 1452 GASOLINE & OIL RES I -- C(UL) T90 NYLON

OR TWN75 FT1

This product complies with European Directive 2002/95/EC (RoHS)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

Wire is packaged on standard metal or wooden reels depending on the putup - consult factory.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name		 	_
Customer Appro	val	 	_

Specification Issue Date: October 16, 2009