



M1-8SFP

Industrial Networking:Industrial Ethernet:MACH100:Media modules

Delivery informations	
Availability	available
Document created at	22.05.2009
Product description	
Description	Media module for modular, managed, Industrial Workgroup Switch MACH100 100 BASE-X with SFP slots
Type	M1-8SFP
Order No.	943 970-301
Network size - length of cable	
Twisted pair (TP)	0 - 100m
Multimode fiber (MM) 50/125 µm	cf. SFP LWL module M-FAST SFP-MM/LC
Multimode fiber (MM) 62.5/125 µm	cf. SFP LWL modul M-FAST SFP-MM/LC
Single mode fiber (SM)9/125 µm	cf. SFP LWL-Modul M-FAST SFP-SM/LC and M-FAST SFP-SM+/LC
Single mode fiber (LH)9/125 µm (long haul transceiver)	cf. SFP LWL modul M-FAST SFP-LH/LC
Power requirements	
Power consumption	11 W (incl. SFP module)
Ambient conditions	
Operating temperature	0° - +50°C
Storage/transport temperature	-20° - +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	109.33 years (MIL-HDBK-217F Gb 25°C)
Mechanical construction	
Dimensions (W x H x D)	138 x 90 x 42
Mounting	Media Module
Weight	0.13 kg
Protection class	IP20
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508 (pending)
Scope of delivery and accessories	
Scope of delivery	Media module, user manual