



Model #: RS-1215-RA

**Power Strip - Multiple outlets wherever you need them**

### Highlights

- Outlets placed at **right angle** to accommodate bulky transformers
- 12 widely spaced outlets (6 front / 6 rear)
- Designed for standard 19-in. racks (1U high)
- 15-ft. cord
- 15A circuit breaker



### Description

Tripp Lite's ☐  
are configurabl☐  
EIA standar☐  
enclosures, netw☐  
AC power cord and lighted power switch with cover that prevents risk of accidental turn-off.

PLUG/OUTLETS: Input: NEMA 5-15P

Output: 12 x NEMA 5-15R (6 front/6 rear)

ELECTRICAL: 120V AC, 50/60Hz, 20A (Requires NEMA 5-15R wall receptacle)

FORMAT: 19-in. rackmount (uses 1 rack space/1U), wallmount, under-counter and more

#### Applications

- Offers multiple out☐  
PC systems, tel☐  
derived AC power to protected equipment.

#### Package Includes

- RS-1215-RA 1U Rackmount Power Strip
- Instruction manual with warranty information

### Features

- Versatile ☐  
Uses one rack space (1U) in standard 19-in. rack ("zero U" mounting possible in many racks)  
☐  
12 x NEMA5-15R output receptacles (6 front/6 rear)  
15-ft. AC cord with NEMA5-15P plug  
Right-angle outlet orientation with ground pin at the bottom

Lighted power switch confirms power on/off status  
 Snap-in switch guard prevents accidental turn off  
 15A electrical capacity with circuit breaker  
 120V AC, 50/60Hz electrical compatibility

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120VAC
Frequency compatibility	50/60Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Outlet quantity / type	12 NEMA 5-15R
Outlet orientation	6 front-facing / 6 rear-facing, all with ground pin oriented to the bottom (when viewed in 1U rackmount configuration)
INPUT	
Input connection type	NEMA 5-15P
Input cord length (ft.)	15
Input cord length (m)	4.572
Recommended Electrical Service	15A 120V
LEDS ALARMS & SWITCHES	
Switches	Red illuminated - positon switch controls power to all outlets
Locking switch cover	Transparent locking switch cover prevents accidental shutoff
PHYSICAL	
Unit Dimensions (HWD/in)	1.75 (1U) x 17.5 x 4.5
Unit Dimensions (HWD/cm)	4.445 x 44.45 x 11.4
Material of construction	Sheet metal
Form factors supported	1U rackmount, wall-mount and undercounter installation supported
Receptacle Color	Black
AC line cord color	Black
SPECIAL FEATURES	
TVSS grounding	Back panel nut-and-bolt grounding lug
CERTIFICATIONS	
UL1363 (Power Tap)	UL1363 (UR status)
cUL / CSA (Canada)	cUL
WARRANTY	
Product warranty	Lifetime