



International Components Corporation

Tel: 631-952-9595 • 800-645-9154 • Fax: 631-952-9597 • Email: oemsales@icc107.com



SUB-MINIATURE LOW PROFILE ROUND SPEAKERS

Part Number: S200RL

MODEL NUMBER	S200RL
FRAME DIAMETER (MM)	50
FRAME DEPTH (MM)	9.0
MATERIAL - CONE / FRAME	PAPER / METAL
MAGNET TYPE	RARE EARTH
MAGNET: SIZE (MM) - WEIGHT (OUNCES/GRAMS)	12.5 x 1.5 - 0.056 / 1.4
RATED POWER (WATTS): Nom. / Max.	0.25 / 0.5
VOICE COIL IMPEDANCE (OHMS)	8 ± 15% @ 1000 Hz 1V
RESONANT FREQUENCY (Hz) Without Baffle	450 ± 20%
FREQUENCY RESPONSE (Hz)	Fo - 4500
OUTPUT SOUND PRESSURE LEVEL (S.P.L.)	84 ± 3 dB
MEASURED AT:	0.2W @ 50CM
MEAN VALUE AT:	800,
OPERATION (MUST BE NORMAL)	POLARITY: DIAPHRAGM SHALL MOVE FORWARD WHEN APPLYING A POSITIVE DC CURRENT TO THE "+" (OR MARKED) TERMINAL. *SPEAKER MUST MEET NORMAL OPERATION AND BUZZ & RATTLES SPECIFICATIONS
BUZZ & RATTLES (MUST BE NORMAL)	
DISTORTION @ RATED POWER INPUT	
LOAD TEST (WHITE NOISE)	
HUMIDITY TEST	

HEAT TEST
OUTSIDE DIAMETER OF YOKE SEAT (MM)
OUTSIDE DIAMETER (ELIMINATE RIM)
BAFFLE OPENING (MM)
THICKNESS OF RIM (MM)
NET WEIGHT (OUNCES/GRAMS)

■ **DIMENSIONS**

■ **TYPICAL FREQUENCY RESPONSE CURVE**

[Return to top](#)

All contents are Copyright © 1999 by International Components Corporation,
All rights reserved.
This site was developed and is maintained by Promptweb.com. For
information, concerns or comments send e-mail to the webmaster.
(webmaster@pw2.com)
