

AZ9321

20 AMP MINIATURE PC BOARD RELAY



FEATURES

- High performance
- 6 kV lightning surge withstand
- Flux tight and sealed versions available
- Class F insulation system standard
- UL, CUR file E44211, TÜV 50100775

CONTACTS

Arrangement	SPST - N.O. (1 Form A) SPDT (1 Form C)
Ratings	Form A and C Max. switched power: 480 W or 4709 VA Max. switched current: 16 A DC, 20 A AC Max. switched voltage: 30 VDC or 277 VAC
Rated Load	1 Form A 20 A at 125 VAC, Res., 100k cycles [1][2] 17 A at 277 VAC, Res., 100k cycles [2] 15 A at 125 VAC, Res., 100k cycles [1][2] 16 A at 250 VAC, Res., 50k cycles [1] 1HP at 250 VAC [1][2] 1HP at 125 VAC [2] TV-8 at 125 VAC [1] 1 Form C 20 A at 125 VAC Res. 100k cycles N.O. [1][2] 20 A at 125 VAC Res. 50k cycles N.C.[2] 20 A at 125 VAC Res. 17k cycles N.C.[1] 17 A at 125 VAC Res. 50k cycles N.C.[1] 17 A at 277 VAC Res. 100k cycles N.O. [2] 15 A at 277 VAC Res. 50k cycles N.C. [2] 1 HP at 250 VAC N.O. [1][2] 1 HP at 125 VAC N.O. [2] 1/2 HP at 125 VAC N.C. [2] 1/2 HP at 277 VAC N.C. [2] TV-8 at 125 VAC N.O./ N.C. [1]
UL/CUR	1 Form A 20 A at 125 VAC Res., 80k cycles [1][2] 16 A at 250 VAC Res., 80k cycles [1][2] 1 Form C 16 A at 250 VAC N.O. Res., 50k cycles[1][2] 10 A at 250 VAC N.C. Res., 50k cycles[1][2]
TÜV	1 Form A 20 A at 125 VAC Res., 80k cycles [1][2] 16 A at 250 VAC Res., 80k cycles [1][2] 1 Form C 16 A at 250 VAC N.O. Res., 50k cycles[1][2] 10 A at 250 VAC N.C. Res., 50k cycles[1][2]
Material	Silver tin oxide [1] or silver nickel [2] (gold plating available)

GENERAL DATA

Life Expectancy Mechanical Electrical	1x10 ⁷ 5 x 10 ⁴ at 20 A 120 VAC Res.
Operate Time	10 ms max.
Release Time	5 ms max. (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	3000 Vrms contact to coil 1000 Vrms across contacts
Insulation Resistance	100 megohms min. at 500 VDC, 50% RH
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage -40°C(-40°F) to 95°C(203°F) -40°C(-40°F) to 155°C(311°F)
Vibration	0.062" DA at 10–55 Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (500°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	14 g

COIL

Power At Pickup Voltage Max Continuous Dissipation	203 mW 1.4 W at 20°C (68°F)
Temperature Rise (at nominal coil voltage)	20°C (36°F)
Temperature	Max. 155°C (311°F)

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Unsealed relays should not be dip cleaned.
4. Specifications subject to change without notice.



AMERICAN ZETTLER, INC. www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

4/16/07W

AZ9321

RELAY ORDERING DATA

STANDARD RELAYS				ORDER NUMBER*	
COIL SPECIFICATIONS				ORDER NUMBER*	
Nominal Coil VDC	Max. Continuous VDC	Coil Resistance	Must Operate VDC	1 Form A (SPST-N.O.)	1 Form C (SPDT)
5	10.0	70 ±10%	3.8	AZ9321-1A-5DF	AZ9321-1C-5DF
6	12.0	100 ±10%	4.5	AZ9321-1A-6DF	AZ9321-1C-6DF
9	18.0	225 ±10%	6.8	AZ9321-1A-9DF	AZ9321-1C-9DF
12	24.0	400 ±10%	9.0	AZ9321-1A-12DF	AZ9321-1C-12DF
18	36.0	900 ±10%	13.5	AZ9321-1A-18DF	AZ9321-1C-18DF
24	48.0	1,600 ±15%	18.0	AZ9321-1A-24DF	AZ9321-1C-24DF
48	80.4	6,400 ±15%	36.0	AZ9321-1A-48DF	AZ9321-1C-48DF

*Replace "-1A" or "-1C" with "-1AE" or "-1CE" for silver tin oxide contacts. Replace "F" with "EF" for epoxy sealed version.
 Replace "F" or "EF" with "AF" or "AEF" for gold plated contacts.

MECHANICAL DATA

Outline Dimensions

Top view dimensions: .827 [21] (width), .630 [16] (width), .157 [4] (height), .079 [2.00] (lead width), .480 [12.20] (lead spacing), .799 [20.3] (height), .236 [6.00] (lead spacing).

Side view dimensions: .089 [2.25] (lead height), .236 [6.00] (lead spacing).

Detail view dimensions: .012 [0.30] (lead thickness), 2x.039 [1.00] (lead width), 2x.020 [0.50] (lead spacing), .039 [1.00] (lead thickness), 2x.020 [0.50] (lead spacing), 2x.018 [0.45] (lead spacing).

PC Board Layout

FORM "A" dimensions: .079 [2.00] (lead width), .157 [4.00] (lead width), .089 [2.25] (lead height), .236 [6.00] (lead spacing), .472 [12.00] (lead spacing), 2x.039 [ø1.0] (lead diameter), .480 [12.20] (lead spacing), 2x.051 [ø1.3] (hole diameter).

FORM "C" dimensions: .079 [2.00] (lead width), .157 [4.00] (lead width), .089 [2.25] (lead height), .236 [6.00] (lead spacing), .472 [12.00] (lead spacing), 2x.039 [ø1.0] (lead diameter), .480 [12.20] (lead spacing), 3x.051 [ø1.3] (hole diameter).

Wiring Diagram

FORM "A" wiring diagram shows terminals 1, 2, 3, 4, and 5. Terminal 1 is the coil, 2 is the common, 3 is the normally open contact, 4 is the normally closed contact, and 5 is the ground.

FORM "C" wiring diagram shows terminals 1, 2, 3, 4, and 5. Terminal 1 is the coil, 2 is the common, 3 is the normally open contact, 4 is the normally closed contact, and 5 is the ground.



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM