

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 2465C
Page 1 of 2 Pages

Issue: 3
Issue Date: 4/13/2005
Effective Date: 6/1/2005

A. Construction

Diameters

- 1) Component 1 2 X 1 COND
 a) Conductor 20 (7/28) AWG TC
 b) Insulation 0.015" Wall, Nom. PVC 0.068
 (1) Color(s)

Cond	Color	Cond	Color	Cond	Color
1	WHITE	2	GREEN		

- 2) Component 2 1 X 1 PAIR
 a) Conductor 20 (7/28) AWG TC
 b) Insulation 0.015" Wall, Nom. PVC 0.068
 (1) Color(s)

Pair	Color	Pair	Color	Pair	Color
1	BLACK-RED				

- c) Cabling 2 COND Cabled
 Individually Applied:
 d) Shield: Alum/Mylar Tape, 25% Overlap, Min.
 (1) Foil Direction Foil Facing Out
 (2) Drain Wire 20 (7/28) AWG TC
 3) Cable Assembly 3 Components Cabled
 a) Twists: 4.8 Twists/foot (min)
 b) Core Wrap Clear Mylar Tape, 25% Overlap, Min.
 4) Jacket 0.030" Wall, Nom.,PVC 0.240 (0.257 Max.)
 a) Color(s) GRAY
 b) Print ALPHA WIRE-* P/N 2465C 4/C 20 AWG
 SHIELDED 75C (UL) TYPE CM --- LLXXXXXX CSA TYPE
 CMG FT4 ROHS
 * = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- 1) UL CM 75°C
 2) CSA International CMG 60°C
 3) EU Directive 2002/95/EC(RoHS):
 All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.
 4) California Proposition 65: The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

C. Physical & Mechanical Properties

- 1) Temperature Range -20 to 75°C
 2) Bend Radius 10X Cable Diameter
 3) Pull Tension 44 Lbs, Maximum

D. Electrical Properties (For Engineering purposes only)

- 1) Voltage Rating 300 V_{RMS}
 2) Component 1
 a) Inductance 0.19 µH/ft, Nominal
 b) Mutual Capacitance 31 pf/ft @1 kHz, Nominal

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 2465C
Page 2 of 2 Pages

Issue: 3
Issue Date: 4/13/2005
Effective Date: 6/1/2005

- c) Conductor DCR 10.1 Ω /1000ft @20°C, Nominal
- 3) Component 2
 - a) Characteristic Impedance 45 Ω
 - b) Inductance 0.19 μ H/ft, Nominal
 - c) Mutual Capacitance 50 pf/ft @1 kHz, Nominal
 - d) Ground Capacitance 90 pf/ft @1 kHz, Nominal
 - e) Conductor DCR 10.1 Ω /1000ft @20°C, Nominal
 - f) Ind. Shield DC Resistance 9 Ω /1000ft @20°C, Nominal

E. Other

- 1) Packaging
 - a) 1000 FT
 - b) 500 FT
 - c) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.