


Current Batteries

Datasheet	Picture	Size	Voltage (nom.)	ANSI	IEC	Diam. (mm)	Weight (g)	Height (mm)	Length (mm)	Width (mm)
1209		Lantern	6	908D	4R25	N/A	600	115	68.2	68.2


Eveready 1209

6V

SUPER HEAVY DUTY



Industry Standard Dimensions



THIS BATTERY WILL PASS FREELY THROUGH A CYLINDRICAL TUBE 82.6 DIAMETER x 101.6 LONG.

Chemical System: Zinc-Manganese Dioxide (Zn/MnO₂)
(No Added Mercury or Cadmium)

Designation: ANSI-908D, IEC-4R25
Battery Voltage: 6.0 Volts
Operating Temp: -18°C to 55°C (0°F to 130°F)
Average Weight: 600 grams (21.2 oz.)
Volume: 492 cubic centimeters (30 cubic inch)
Average Capacity: 11 Ah to 0.8 volts / cell
(Rated at 25mA continuous at 21°C)
Cell: Four No. 60 (size "F") in series
Jacket: Plastic
Terminal: Coil Spring


INTERNAL RESISTANCE VS. TEMPERATURE

The measurement is an approximation of the battery's actual internal resistance. It is sensitive to the loads and operator technique.


Schedule: Background Load 600 ohms
 Pulse Load 10 ohms
 Pulse Duration 1 second

Temperature	Typical Ri (ohms)
45°C (113°F)	0.7
21°C (70°F)	0.9
0°C (32°F)	1.0
-21°C (-4°F)	10.0

CONSTANT RESISTANCE PERFORMANCE
Typical Service



CONSTANT CURRENT DISCHARGE
Typical Service



Important Notice

This data sheet contains information specific to batteries manufactured at the time of its publication.
Contents herein do not constitute a warranty.