

# SIMM Tester EPROM Eraser

## Model 850 EPROM ERASER

The Model 850 is a UV- EPROM eraser featuring small dimensions, high erasing efficiency, and simple operation. Up to five EPROM's in 40-pin DIP packages can be erased simultaneously. A built-in timer is preset to an optimum erasing period.



850



851

## Specifications

	851	models 850
Timer Setting	60 min.	15 min.
Timer Setting	100-120VAC 50/60Hz	12VDC/500mA (AC/DC adapter included)
UV bulb wattage	10W	4W
Dimensions	15.5 x 6 x 3.25" (394 x 150 x 80mm)	6.2 x 2.72 x 1.45 (158 x 69 x 37mm)
Weight	8.8 lbs. (4kg)	9 oz. (255g)
Supplied	AC Power cord, Manual	AC/DC adapter, Pad, Manual

**One Year Warranty**

## Model 898A SIMM Tester

B+K Precision Model 898A is a stand alone, portable device that tests a wide variety of Single-In-Line Memory Modules (SIMM) and Dual-In-Line Memory Modules. It tests many DRAM/SDRAM modules.

B+K Precision Model 898A was generally designed as a field tool for computer integrators, dealers, small manufacturing companies, service professionals, and qualified computer end users. It is portable and simple to operate because it is built on the bases of high level electronic technology. User interface is very simple and intuitive: a dual line Liquid Crystal Display (LCD) and large buttons allow easy operation through a multi-level menu system. The 898A uses a high-speed FPGA to execute as many as six different types of memory tests.



898A

## Model 851 Deluxe EPROM Eraser

The model 851 is a heavy duty EPROM eraser that can simultaneously erase up to 40 twenty-four pin EPROM's. It is constructed of an all-metal case plus an advanced designed chip drawer that prevents UV radiation from being a hazard to the user. The chip drawer is lined with conductive foam to prevent electrostatic damage to the chips.

- Indicator light when erasing
- Power safety switch inside the drawer shuts off unit whenever the drawer is opened
- Large capacity
- One year warranty

## Specifications

	898A	model
Power Source	12V, 2.0A AC/AC adapter:	
Dimension (L x W x H)	7 x 6 x 2.5" (178 x 152 x 64mm)	
Weight	3.5 lbs. (1.59kg) with AC power adapter	
Operating temperature	10° to 50°C, 20% to 80% RH noncondensing	

## Accessories

SUPPLIED: AC/AC wall adapter 115VAC(or 230VAC),  
Registration and warranty card and manual SM-168-SD  
Optional Adapter and Accessories:  
SM-30 Adapter for 30-pin SIMM DRAM  
SM-72 Adapter for 72-pin SIMM  
SM-144-SD Adapter for 144-pin SODIMM Unbuffered SDRAM (3.3V)  
SM-144-3.3V Adapter for 144-pin SODIMM Unbuffered DRAM (3.3V)  
SM-168-SD Adapter for 168-pin DIMM Unbuffered SDRAM (3.3V)  
SM-168-3.3 Adapter for 168-pin DIMM Unbuffered DRAM (3.3V)  
SM-168B-5V Adapter for 168-pin DIMM Buffered DRAM (5V)  
RS-CBL RS-232 DB9 Cable

**One Year Warranty**

## Features

	898A	model
Testing Memory Types and parameters	- Page Mode, Static Column Mode, EDO, and SDRAM types based:	- Timing related failures
- SIMM 30-pin, 8/9 bits		- Data retention errors
- SIMM 72-pin, 32/36 bits		- Intermittent failures
- SODIMM 144-pin 64 bits		User Configuration Test Modes:
- DIMM 168-pin 64/72 bits		- Walking Bit 0s
Error Detection and Identification		- Walking Bit 1s
- Single data bits		- Marching Up
- Power and noise related failures		- Marching Down
- Solder opens and shorts		- Checkerboard
		- Inversed Checkerboard
		Made and Supported in the USA