

WORLDWIDE

PRODUCTS



CML

INNOVATIVE TECHNOLOGIES

WHERE INNOVATION COMES TO LIGHT

[Home](#)

[About CML](#)

[Service](#)

[Media Center](#)

[Contact](#)

[Access CML](#)

## Products

### Aviation Neon Lamps

CML's line of neon lamps represents of the most economical forms of 'power on' indication. They provide superior performance under shock and vibration conditions.



**Part Number:** A1A (NE-2)

**Serial Number:** W T-2

**Type:** T-2

**Base:** Wire Terminal

**Max. Striking Volts (AC):** 65

**Max. Striking Volts (DC):** 90

**Design Current Max:** 0.6

**Series Resistor Value 100\_120:** 100KW1/4 W

**Series Resistor Value 220\_250:** 540KW1/3 W



**Avg Life:** 25000

**Brightness:** Std

**Military Reference:**

**RoHS Status:** Yes

**Neon Indicator Lamps**

Configuration	Part Number	Old Ref. Number	Design Current mA	Maximum Breakdown Voltage	
				VAC	VDC
<b>Wire Terminal-Standard Brightness</b>					
	2ML	NE -38S	0.3	65	90
	A1A	NE -2	0.6	65	90
	A1A-T	NE -2T	0.6	65	90
	A1B		0.3	65	90
	A1D		0.3	65	90
	A1D-T		0.3	65	90
	K4A	AR -9	0.3	80	115
	A2B	NE -2V	0.7	65	90
	A2B-T	NE -2VT	0.7	65	90
	A9A	NE -2E	0.7	65	90
	A9A-T	NE -2E T	0.7	65	90
	A9A-C	NE -2E 1	0.7	65	90
	A9A-C T	NE -2E 1T	0.7	65	90
<b>Wire Terminal-High Brightness</b>					
	1MH	NE -38	1.2	95	135
	A1C		1.2	95	135
	A1C -T		1.2	95	135
	G2B -1		1.2	95	135
	G2B -2		1.4	95	135
	A3C	NE -2U	1.9	95	135
	A3C -T	NE -2UT	1.9	95	135
	C2A	NE -2H	1.9	95	135
	C2A-T	NE -2HT	1.9	95	135
	C2A-C	NE -2H1	1.9	95	135
	D2A		2.6	95	135

Footnotes

- Life value is to approximately 50% of initial light output. Values shown apply to use on AC unless otherwise shown. Life on DC is approximately 60% of AC values when DC current is equal to RMS AC value. When equal DC and RMS AC voltages and equal resistances are utilized, life will be approximately the same.
- For DC operation of high brightness lamps use a minimum of 150 circuit volts. Maximum initial breakdown voltage 95 VAC, 135 VDC in light.
- Tinned leads.
- High brightness.
- Formed tip.
- Dark effect reduced.
- Lamp drops through a Ø.310" cylinder of .500" minimum length.

Series Resistor				Average Useful Life	Dimensions inches			Footnotes
100-125V		220-250V			A(Max.)	B(Max.)	C(Min.)	
Ohms	W	Ohms	W					
<b>Wire Terminal-Standard Brightness</b>								
100K	1/4	220K	1/3	12,000	.156	.395	1.00	1,5
100K	1/4	540K	1/3	25,000	.244	1.00	1.00	1,5
100K	1/4	540K	1/3	25,000	.244	1.00	1.00	1,3,5
220K	1/4	540K	1/3	25,000	.244	.500	1.00	1,5
220K	1/4	540K	1/3	25,000	.244	.500	1.00	1,5,6
220K	1/4	540K	1/3	25,000	.244	.500	1.00	1,3,5,6
220K	1/4	540K	1/3	50	.244	.980	1.00	14
100K	1/4	220K	1/3	25,000	.244	.750	2.00	1,5,6
100K	1/4	220K	1/3	25,000	.244	.750	2.00	1,3,5,6
100K	1/4	220K	1/3	25,000	.244	.750	2.00	1,5
100K	1/4	220K	1/3	25,000	.244	.750	2.00	1,3,5
100K	1/4	220K	1/3	25,000	.244	.750	1.00	1,5
100K	1/4	220K	1/3	25,000	.244	.750	1.00	1,3,5
<b>Wire Terminal-High Brightness</b>								
47K	1/4	150K	1/3	12,000	.156	.395	1.00	1,4,5
47K	1/4	150K	1/3	25,000	.244	.500	1.00	2,4,5,6,8
47K	1/4	150K	1/3	25,000	.244	.500	1.00	2,3,4,5,6,8
47K	1/4	150K	1/3	15,000	.244	.500	1.00	1,4,5,13
39K	1/4	120K	1/3	15,000	.244	.750	1.00	1,4,5,13
30K	1/4	100K	1/3	25,000	.244	.750	2.00	2,4,5,6,8,9
30K	1/4	100K	1/3	25,000	.244	.750	2.00	2,3,4,5,6,8,9
30K	1/4	100K	1/3	25,000	.244	.750	2.00	2,4,5,6,8
30K	1/4	100K	1/3	25,000	.244	.750	2.00	2,3,4,5,6,8
30K	1/4	100K	1/3	25,000	.244	.750	1.00	2,4,5,6,8
22K	1/4	68K	1/3	25,000	.244	.980	1.00	2,4,5,6,8,10

- 8. Life values shown apply to use on AC unless otherwise shown. End of life occurs when breakdown voltage increases to line voltage and lamp will no longer start. With equal DC and RMS AC current, life will be somewhat lower than the 60% value quoted for standard brightness lamp.
- 9. Maximum breakdown voltage in total darkness 100VAC.

- 10. Minimum current for stable operation 1.5mA.
- 11. Resistor included in Base.
- 12. Caution: Bulb may shatter and/or circuit may be damaged without external series resistance.
- 13. Green fluorescent.
- 14. Argon gas filled.