


164TL11 Product Details

[Share](#) [Print](#) [Email](#)



164TL11

TE Internal Number: 3-1437569-4

Active

Industrial Panel Mount Switches and Lights

[Converted to EU RoHS/ELV Compliant](#)
(Statement of Compliance)

Product Highlights:

- Switch
- Switch Type = Pushbutton
- Operating Function = Momentary
- Contact Rating = 5A
- 1 Normally Open and 1 Normally Closed Type of Contact

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)

[Request Sample](#)

[Find Similar Products](#)

[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch
- Series = Command
- Actuator Style = Rectangular

Mechanical Attachment:

- Panel Cutout = 16mm Diameter

Electrical Characteristics:

- Contact Rating = 5A
- Oil-Tight = No

Termination Features:

- Seal Type = IP65

Body Features:

- Switch Type = Pushbutton
- Used With = Lens Model 64T(*) (where * equals (2) Red, (3) Orange, (4) Yellow, (5) Green, (6) Blue, or (9) White., T1 3/4 midget flanged base lamps.
- Mount Style = Panel

Configuration Features:

- Operating Function = Momentary
- Type of Contact = 1 Normally Open and 1 Normally Closed
- Number of Actuators = Single
- Illuminated = Yes

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Other:

- Brand = Alcoswitch
- Comment = Order Lamp Separately.; Order Lens Set Separately.