



What can we help you find?

[Products](#) |
 [Industries](#) |
 [Resources](#) |
 [About TE](#) |
 [My Account](#) |
 [Innovation](#) |
 [Support Center](#)

KRPA-11DN-110 Product Details

[Share](#) |
 [Print](#) |
 [Email](#)



KRPA-11DN-110

TE Internal Number: 4-1393104-9

Active

Industrial Relays (General Purpose)

Not EU RoHS or ELV Compliant

Product Highlights:

- KRPA Series
- Contact - Current Class = 5A to 10A Class, Less Than 16A
- Contact - Rated Current = 10 A
- Terminal Type = Plug-in
- Contact - Arrangement = 2 Form C (CO)

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) |
 [Request Sample](#) |
 [Find Similar Products](#) |
 [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • KRPA, KRP, KA, KR 5 to 10 Amp General Purpose Relay (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Additional Product Images:</p> <ul style="list-style-type: none"> • Schematic • Wiring Diagram <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Series = KRPA • Terminal Type = Plug-in <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Contact - Current Class = 5A to 10A Class, Less Than 16A • Contact - Rated Current (A) = 10 • Contact - Limiting Continuous Current (A) = 10 • Contact - Limiting Making Current (A) = 10 • Contact - Limiting Breaking Current (A) = 10 • Insulation - Initial Dielectric Between Coil/Contact Class = 500V to 1000V Class • Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000 • Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 1000 • Contact - Rated Voltage (VAC) = 240 • Contact - Limiting Short-Time Current (A) = 10 • Contact - Switching Recommended Load, Min. = 300mA at 12V • Coil - Rated Voltage (VDC) = 110 • Coil - Resistance (Ω) = 10000 • Coil - Rated Power, DC (mW) = 1200 • Coil - Rated Power Class = 1W to 1.5W Class • Insulation - Initial Dielectric Between Adjacent Contacts (V rms) = 1000 • Insulation - Initial Insulation Resistance (MΩ) = 1000000 <p>Dimensions:</p> <ul style="list-style-type: none"> • Mechanical - Length Class = 35mm to 40mm Class • Length (mm [in]) = 35.70 [1.406] • Mechanical - Width Class = 30mm to 40mm Class 	<p>Body Features:</p> <ul style="list-style-type: none"> • Mount Type = Socket • Weight (g [oz]) = 85.00 [2.988] <p>Contact Features:</p> <ul style="list-style-type: none"> • Contact Material = AgCdO • Contact - Number of Poles = 2 <p>Configuration Features:</p> <ul style="list-style-type: none"> • Contact - Arrangement = 2 Form C (CO) • Coil - Magnetic System = Monostable, DC • Coil - Special Features = UL Coil Insulation Class B, Electrical Indicator <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not relevant for lead free process • Approved/Registered Standards = CSA, UL <p>Environmental:</p> <ul style="list-style-type: none"> • Environmental - Category of Protection = RTI • Environmental - Ambient Temperature, Max. (°C [°F]) = 70 [158] • Environmental - Ambient Temperature Class = 50°C to 70°C Class <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Tray <p>Other:</p> <ul style="list-style-type: none"> • Brand = Potter & Brumfield

- Width (mm [in]) = 35.70 [1.405]
- Mechanical - Height Class = >50mm Class
- Height (mm [in]) = 50.80 [2.000]

- Accessories/Socket Type = Track mount Socket, DIN-rail Socket

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

