
Pins and Terminals



Terminals: Vector Wiring Terminals are useful for breadboarding or prototyping using Vectorbord Plugbords^{IM} and accessories. Individual stamped and/or machine terminals are provided in convenient package quantities. Tools for insertion and staking are also available.

T46 - Press-In Terminals for 0.042" diameter holes


- Single and double-tailed (accessible from both sides) wire-wrap terminals
- 0.025" square posts
- Provides secure contact without soldering or staking
- Rectangular base with stepped shank presses into plain or plated-thru holes and is retained without etching or soldering
- Pointed ends slide neatly into all wrapping bits




T44, T68 Bifurcated Miniwrap Terminals for 0.042" holes



- Wire-Wrap tail with two-pronged receptacle for wires or leads
- 0.025" square posts
- Rectangular terminal with stepped shank presses securely into plated or unplated holes, requires no staking or soldering
- Bifurcated end holds soldered leads securely
- T44: maximum 0.021" diameter leads or 24 gage wires
- T68: maximum 0.032" diameter leads or 20 gage wires






Insertion Tool: A13-1 Insertion Tool: A13



Terminal: Tin Plate Part No.	Terminal: Gold Plate Part No.	Package Qty	Hand Insertion Tool	
T44/C T44/M T46-2-9/M T46-3-9/C T46-3-9/M T46-4-9/C T46-4-9/M T46-5-9/C T46-5-9/M T49/C T49/M T68/C T68/M T68A/M	T44-1/C T44-1/M T46-3A9/M T46-4A9/M T49A/C T49A/M T68-1/M	100 1000 1000 1000 1000 1000 1000 1000	A13 A13 P133A P133A P133A P133A P133A P133A P156 P156 A13-1 A13-1	P133A
T46-5-9/M T49/C T49/M T68/C T68/M	T49A/M	1000 100 1000 1000 100	P133A P156 P156 A13-1 A13-1	


T49 - Trifurcated Klipwrap Terminals for 0.042" diameter holes

- Wire-wrap tail with three-pronged receptacle for wires or leads
- 0.025" square posts
- Wires or leads are crimped into receptacle on component side, secured for soldering
- Holds 0.018" 0.025" diameter leads or 22 gage wires in lower slot, 0.032" - 0.040" diameter leads or 17 gage wires in upper slot
- Overall length 0.650", 0.215" above 0.062" thick board with 0.373" below the board




T125, T126 -Wire-Wrap Terminals for .042" diameter holes

 Pressfit wire-wrap terminals, ideal for connecting voltage and ground holes in Vectorbord plus[™] and Pads & Planes[™] patterns



 3-level terminals: Part No. T126



Ð				
Part No.	Α	В		
T125/C	.560"	.529"		
T126/C	.700"	.669"		
Packages of 100 each				



7: