

# **Stripmaster Wire Stripper #8 to #12 AWG**

Catalog # 45-090



# Features

- Knife-type blades
- Cleanly strips wire up to 7/8 in. (22mm)
- One-third less hand pressure for each strip
- Eliminates nicking, cutting, and fraying of wire
- Wire Gripper holds wire centered in hole



## Stripmaster<sup>®</sup> and Stripmaster<sup>®</sup> Lite Wire Strippers

- One-step stripping enhances productivity
- Spring-action motion increases leverage and reduces operator fatigue
- Precision-ground, knife-type blades provide clean, accurate stripping
- Sturdy die cast frame provides long-term durability
- Wire gripper holds wire securely in position
- Stripmaster<sup>®</sup> Lite designed for smaller hands 3/4 the size of the standard Stripmaster<sup>®</sup>

Stripmaster® Wire Strippers and Knife-Type Blades





MUMDOUN

And And



Knife-type stripping blades have form-ground holes which penetrate the insulation like a knife, giving a clean insulation

Gripper holds the wire

securely in position.

Specifications — Stripping Hole Diameter (Inches)										Replacement Blades (Pair)			
Wire Size AWG													
8	10	12	14	16	18	20	22	24	26	28	30	Cat. No.	Cat. No.
.159	.141	.106										45-090* or 45-290**	L-4419
	.144	.105	.085	.073	.073							45-091	L-4420
	.144	.113	.090	.072	.061	.048	.048					45-092* or 45-292**	L-4421
			.090	.072	.061	.039	.039					45-093	L-4422
.198												45-096	L-4453
				.072	.061	.048	.039	.032	.026			45-097	L-4994
						.048	.039	.032	.026	.021	.016	45-098	L-5361
.198	.167			.062	.055							45-099	L-8763
.1	159	159 .141 .144 .144 198	159 .141 .106 .144 .105 .144 .113 .148 .113 .198	8  10  12  14    159  .141  .106	8  10  12  14  16    159  .141  .106      .144  .105  .085  .073    .144  .113  .090  .072    .144  .113  .090  .072    198  .  .  .  .	8  10  12  14  16  18    159  .141  .106  -  -    .144  .105  .085  .073  .073    .144  .105  .085  .073  .073    .144  .113  .090  .072  .061    198  -  -  -  -    198  -  .073  .072  .061	8  10  12  14  16  18  20    159  .141  .106	8  10  12  14  16  18  20  22    159  .141  .106 <t< td=""><td>8  10  12  14  16  18  20  22  24    159  .141  .106  </td><td>8  10  12  14  16  18  20  22  24  26    159  .141  .106   &lt;</td><td>8  10  12  14  16  18  20  22  24  26  28    159  .141  .106  <t< td=""><td>8  10  12  14  16  18  20  22  24  26  28  30    159  .141  .106   <t< td=""><td>8  10  12  14  16  18  20  22  24  26  28  30  Cat. No.    159  .141  .106  </td></t<></td></t<></td></t<>	8  10  12  14  16  18  20  22  24    159  .141  .106	8  10  12  14  16  18  20  22  24  26    159  .141  .106   <	8  10  12  14  16  18  20  22  24  26  28    159  .141  .106 <t< td=""><td>8  10  12  14  16  18  20  22  24  26  28  30    159  .141  .106   <t< td=""><td>8  10  12  14  16  18  20  22  24  26  28  30  Cat. No.    159  .141  .106  </td></t<></td></t<>	8  10  12  14  16  18  20  22  24  26  28  30    159  .141  .106 <t< td=""><td>8  10  12  14  16  18  20  22  24  26  28  30  Cat. No.    159  .141  .106  </td></t<>	8  10  12  14  16  18  20  22  24  26  28  30  Cat. No.    159  .141  .106

MARION

Stripmaster<sup>®</sup>

Wire Stripper

ed \*\*Blister Card Tolerances +.001 -.005

#### Stripmaster® Lite Wire Strippers and Knife-Type Blades

Specifications — Stripping Hole Diameter (Inches) Wire Size AWG											Replacement Blades (Pair)			
12	14	16	18	20	22	24	26	28	30	16/18	20/22	Cutting Edge	Cat. No.	Cat. No.
		.072	.061	.048	.039								45-671	LB-1001
						.032	.026	.021	.016				45-672	LB-1002
.113	.090	.072	.061 (A	All Strande	ed wire)								45-673	LB-1003
.096	.085	.073	.061 (12 & 14 Solid wire, 16 & 18 Stranded wire)							45-674	LB-1004			
										.072	.048	.250 Wide	45-675	LB-1005

Tolerances +.001 -.005

### $\textbf{Coax Stripmaster}^{\circledast} \textbf{ Wire Strippers and Blades}$

Description	Coax Cable Type (RGU)	Repl. Blade Cat. No.	Cat. No.
Coax Stripmaster® for RG-6	RG-6	LB-740	45-262
Coax Stripmaster® for RG-58	RG-58	LB-742	45-264
Coax Stripmaster® for RG-59	RG-59	LB-743	45-265
Coax Stripmaster® for RG-62	RG-62	LB-744	N/A
Coax Stripmaster® for RG-6 QuadShield	RG-6 QuadShield	LA-3953	45-282

Coaxial Cables: two-step strip for termination, jacket and dielectric.

Replacement Frame Assemblies	Cat. No.
For Stripmaster® Wire Strippers	L-5620
For Stripmaster® Lite Wire Strippers	LB-1421

## Stripmaster<sup>®</sup> Wire Strippers with Rectangular Holes



Description	Cat. No.	Replacement Blades (Pair) Cat. No.
For Flat Telephone Cable (.60 in. or 1.52mm)	N/A	LB-1155
For European Flat Lamp Cord	45-089	L-8762
For SP-SPT Lamp Cord	45-095*	L-4452

\*Also strips 2- and 3-conductor low-voltage wire used in G.E. and Touchplate remote control wiring system.

Optional Accessories	Cat. No.
Transparent Adjustable Wire Stop (for Stripmaster® Wire Strippers)	L-5270
Transparent Adjustable Wire Stop (for Stripmaster® Lite Wire Strippers)	LB-1195
Replacement Moveable Gripper	L-1953