

IDEAL Electrical's line of TKO™ Carbide-Tipped Hole Cutters offer the most efficient and clean cutter replacement for traditional knockouts, by making smooth holes in a fraction of the time at a fraction of the cost. Specifically designed to cut sheet metal, IDEAL TKO™ cutters will even cut stainless steel with their precision engineered ground carbide tips.

The innovative design includes the exclusive SmoothStart™ replaceable pilot drill, which guides the cutter to the surface, avoiding cutter damage and providing smoother holes. With an integral over-drill flange the IDEAL TKO™ prevents cutter penetration beyond the sheet metal. When it comes to quality, performance and durability, IDEAL is the professional's choice for carbide-tipped hole cutters.





Quickly drills precise holes without penetration beyond sheet metal.


Integral arbor provides smooth accurate holes 36-305 10 Pipe 84 Integrated overdrill flange prevents penetration beyond the sheet metal Carbide-tips cut over 200 holes through stainless steel, and outperform HSS cutters and bi-metal hole saws in sheet steel effortlessly ejects slug Exclusive SmoothStart™ pilot drill guides cutter to prevent cutter damage and provide

smooth, more accurate holes.

IDEAL TKO™ provides smoother, more precise hole than

Ejection spring









Exclusive SmoothStart $^{\text{TM}}$ pilot drill guides cutter to prevent damage to cutter head.

Electrician's Kit

Includes cutter heads for all conduit sizes from 1/2 in. to 2 in. conduit, along with two spare SmoothStart™ pilot bits and a convenient carrying case.



Description	Part No.
8-Piece Carbide Hole Cutter Kit-Incudes: Two SmoothStart™ pilot bits, 7/8, 1-1/8, 1-3/8, 1-3/4, 2 and 2-1/2 in. Cutter Heads.	36-314

4-Piece Kit

Includes the 3 most common sizes, along with a spare SmoothStart™ pilot bit and a convenient carrying case.



Description	Part No.
4-Piece Carbide Hole Cutter Kit-Includes: SmoothStart™ pilot bit, 7/8, 1-1/8, and 1-3/8 in. Cutter Heads.	36-311

SmoothStart™ Replacement Pilot Drills





Fits Hole Saws:	Diameter	Drill Depth	Overall Length	Part. No.
3/4 in. to 3-1/2 in.	1/4 in. (6mm)	3/4 in. (19mm)	2 in. (51mm)	36-312
4 in. and 4-1/2 in.	5/16 in. (8mm)	3/4 in. (19mm)	2-3/8 in. (60mm)	36-369

Drilling depth: 3/16 in. (5mm); Effective length: 1/2 in. (12mm)



Integrated over-drill flange prevents penetration beyond the sheet metal.

Carbide-Tipped Hole Cutters

Hole Size	Conduit & Pipe Size	Part No.		
3/4 in. (19mm)	_	36-300		
7/8 in. (22mm)	1/2 in. (22mm) - pushbutton	36-301		
1 in. (25mm)	_	36-302		
1-1/8 in. (29mm)	3/4 in. (19mm)	36-303		
1-7/32 in. (30mm)	7/32 in. (30mm) - pushbutton	36-313		
1-1/4 in. (32mm)	_	36-304		
1-3/8 in. (35mm)	1 in. (25mm)	36-305		
1-7/16 in. (37mm)	_	36-306		
1-1/2 in. (38mm)	_	36-307		
1-3/4 in. (44mm)	1-1/4 in. (32mm)	36-308		
2 in. (51mm)	1-1/2 in. (38mm)	36-309		
2-1/2 in. (64mm)	2 in. (50mm)	36-310		
2-7/8 in. (73mm)	2-1/2 in. (64mm)	36-315		
3-1/2 in. (89mm)	3 in. (76mm)	36-316		
4 in. (102mm)	3-1/2 in. (89mm)	36-317		
4-1/2 in. (114mm)	4 in. (102mm)	36-318		

3/8 in. shank on all hole cutters. Max. Material thickness is 1/8 in.

Available in a full range of sizes from 3/4" to 4½".



To extend the life of your TKO's use cutting oil.

SEE HOW IDEAL TKO HOLE CUTTERS SAVE TIME





Drill Hole & Store

Total time using the IDEAL TKO™

30 Seconds

COMPARED TO THE COMPETITOR







Drill Pilot Hole



knock-out tool More than

Total time using the competitor's

6 Minutes







& Store

IDEAL INDUSTRIES, INC.

1800 S. Prairie Dr., Sycamore, IL 60178, USA / 815-895-5181 • 800-435-0705 in USA