
69802-432LF - PLCC : **Surface Mount Type Sockets**







Specifications

Gen	era
-----	-----

Location Peg	No
Number of contacts	32
Product Style	PLCC
Electrical	
Current rating	1 amp
Resistance (Contact)	20 m ohms max.
Resistance (Insulation)	1000 M ohms min.
Voltage rating	120V AC/DC
Mechanical	
Durability (Mating cycles)	25 Cycles
Insertion force	15 lbs max.
Withdrawal Force	1.5 lbs max.
Mounting	
Mounting style	Surface Mount
Physical	ı
Color (Housing)	Brown
Material (Contact)	Copper Alloy
Material (Housing)	PPS, UL94V-0
Plating (Inner clip / Contact)	150μ" Pure Tin
Underplating (Contact)	40μ" Nickel
Temperature (Range)	-55°C to 125°C
Approvals / Certifications	
Approvals / Certifications	UL Approved
Other Features	
Packaging (Type)	Tape and Reel




TABLE I NO. OF DIM. CONTACTS ±0.2 20 5.08 28 7.62							
20 5.08		DIM. C DIM		DIM. F	DIM. G	DIM. H	DIM. I DIM.
		±0.20 ±0.		±0.10	±0.10	±0.20	±0.20 ±0.2
28 7.62	15.24	16.70 5.0		8.48	8.48	12.70	9.40
	17.78	20.30 7.6		11.02	11.02	15.24	11.94
32 7.62	17.78	22.50 10.		11.02	13.56	17.78	11.94 14.4
44 12.7		27.50 12.		16.10	16.10	20.32	17.02
52 15.2		31.10 15.		18.64	18.64	22.86	19.56
68 20.3		38.30 20.		23.72	23.72	27.94	24.64
84 25.4	35.90	45.50 25.	40 35.90	28.80	28.80	33.02	29.72
	✓		PLCC-XXP-T-SMT-P PLCC-XXP-T-SMT				
69802-1XX							
	./ ./						
			PLCC-XXP-T-SMT-P1			∟s	SEE TABLE II
	*		PLCC-XXP-T-SMT-TF				
	/ /	*	PLCC-XXP-T-SMT-P-				
69802-1XXLF			PLCC-XXP-T-SMT-LF	-			
69802-4XXLF	·	✓	PLCC-XXP-T-SMT-TF	R-LF			
69802-4XX 69802-0XXPT 69802-1XXPT 69802-4XXPT 69802-0XXLF 69802-1XXLF 69802-4XXLF	,		PLCC-XXP-T-SMT-TF PLCC-XXP-T-SMT-P- PLCC-XXP-T-SMT-LF	-PT FR-PT -LF			

