



Interlock extension

Part no.
Article no.

ZVV-T0
022298



Powering Business Worldwide™

Up to four off, 25 mm each, can be plugged onto interlock section

(An equal number of shaft extensions is required for this purpose)

Delivery programme

Product range			Accessories
			Interlock elements
Information about equipment supplied			A max. of 4 units can be put on the interlock section every 25 mm (an equal number of shaft extensions is required for this)
			Use only with T0/T3-.../Z and P1-.../Z design
For use with			UV-T0

Technical data ETIM 4.0

Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Rated permanent current I _u		A	0
Number of poles			0
Conditioned rated short-circuit current I _q		kA	0
Degree of protection (IP), front side			-
Number of auxiliary contacts as change-over contact			0
Interlockable			No
Motor drive integrated			No
Connection type main current circuit			-
Version as emergency stop installation			No
Type of control element			-
Version as main switch			No
Version as switch disconnecter compact			No
Version as safety switch			No
Version as maintenance-/service switch			No
Rated operation power at AC-23, 400V		kWh	0
Rated operation power AC-3, 400 V		kWh	0
Suitable for ground mounting			No
Suitable for front mounting			No
Suitable for front mounting center			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Max. rated operation voltage U _e AC		V	0
Motor drive optional			No
Voltage release optional			No
Device construction			-



Extension shaft

Part no.

ZAV-T0

Article no.

027044



Powering Business Worldwide™

Up to four off, 25 mm each, can be plugged onto switch shaft

Delivery programme

Product range			Accessories
			shaft extension
Information about equipment supplied			A max. of 4 units can be put on the switch shaft every 25 mm
For use with			T0-.../Z, T0-.../V T3-.../Z, T3-.../V P1-.../Z, P1-.../V

Technical data ETIM 4.0

Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Rated permanent current I _u		A	0
Number of poles			0
Conditioned rated short-circuit current I _q		kA	0
Degree of protection (IP), front side			-
Number of auxiliary contacts as change-over contact			0
Interlockable			No
Motor drive integrated			No
Connection type main current circuit			-
Version as emergency stop installation			No
Type of control element			-
Version as main switch			No
Version as switch disconnecter compact			No
Version as safety switch			No
Version as maintenance-/service switch			No
Rated operation power at AC-23, 400V		kWh	0
Rated operation power AC-3, 400 V		kWh	0
Suitable for ground mounting			No
Suitable for front mounting			No
Suitable for front mounting center			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Max. rated operation voltage U _e AC		V	0
Motor drive optional			No
Voltage release optional			No
Device construction			-