Thomas@Betts



Safety Switches T&B Catalog Number:

2TLA050009R1012

UPC Number: 80432583242

Status: Active

Description:

Solenoid locking interlock safety switch featuring power to lock guard holding up to 1800N

nolaing up to 1800N	
Features	
	The MKey 9M series guard locking switches have a slim plastic body design and have been developed with a holding force of 1800N to keep medium guard doors closed until hazards have been removed
	Suitable for applications where immediate unlocking is required at removal or loss of power The high specification plastic body has a high resistance to chemical and washdown solutions and the stainless steel head provides a durable robust protection of the cam interlock
	IP67 enclosure protection is maintained by a double seal lid gasket design and metal fixings
	They have a slim profile and are designed to fit on 50mm (2 in) frame sections or to applications where space is restricted
	The head will rotate to provide up to 8 actuator entry positions An LED is available to indicate lock status
Application	
	Ensures that a machine stops when a door or a hatch is opened
General	
Style Series	Locking Switches MKey 9M
Dimension Information	
L x W x H (mm)	160 x 46 x 45.50
L x W x H (in)	6.30 x 1.81 x 1.79
Packaging	
Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	1.4 lbs. Each
Certifications	
Approvals	C_UL_US, CE, TUV

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com