


## BES M08MH1-PSC20B-S04G BES0028



IND. CONT. EQ  
81U2  
US for use in the secondary of  
a class 2 source of supply  
Environmental - Type 1 Enclosure



### Display/Operation

Function indicator	yes
Power indicator	no

### Electrical connection

Connection	M12x1-Connector, 4-pole, A-coded
Polarity reversal protected	yes
Short-circuit protection	yes

### Electrical data

Hysteresis H max. (% of Sr)	15.0 %
Load capacitance max. at Ue	1 µF
MTTF (40 °C)	880 a
No-load current I <sub>0</sub> max., undamped	5 mA
Operating voltage U <sub>b</sub>	12...30 VDC
Output resistance R <sub>a</sub>	33.0 kOhm + D
Pollution degree	3
Protected against miswiring	yes
Rated insulation voltage U <sub>i</sub>	75 V DC
Rated operating current I <sub>e</sub> DC	200 mA
Rated operating voltage U <sub>e</sub> DC	24 V
Rated short circuit current	100 A
Ready delay t <sub>v</sub> max.	30 ms
Repeat accuracy max. (% of Sr)	5.0 %
Residual current I <sub>r</sub> max.	20 µA
Switching frequency	700 Hz
Utilization category	DC -13
Voltage drop static max.	2.5 V

### Environmental conditions

Ambient temperature	-25...70 °C
---------------------	-------------

Protection type IEC 60529

IP67

### Functional safety

Diagnostic coverage	0 %
Functional safety	no
Mission Time	20 a

### General data

Approval/Conformity	CE cULus EAC
Basic standard	IEC 60947-5-2
Trademark	Global

### Material

Housing material	Brass
Material sensing surface	PA 12
Surface protection	nickel plates

### Mechanical data

Dimension	Ø 8 x 65 mm
Installation	for flush mounting
Size	M8x1
Tightening torque	3 Nm

### Output/Interface

Switching output	PNP Normally open (NO)
------------------	------------------------

### Range/Distance

Assured operating distance S <sub>a</sub>	1.6 mm
---	--------

BES M08MH1-PSC20B-S04G  
BES0028

Range	2 mm
Rated operating distance $S_n$	2 mm
Ripple max. (% of $U_e$ )	15 %
Switching distance marking	■ ■
Temperature drift max. (% of $S_r$ )	10 %

Remarks

Shielded: See installation instructions for inductive sensors with extended range 825357.  
The sensor is functional again after the overload has been eliminated.

For further information on MTTF/B10d, please refer to the MTTF / B10d Certificate.

Specification of the MTTF value and the B10d value do not represent any binding quality and/or life expectancy guarantees.

Connector view



Wiring Diagram

