

SITOP DC UPS MODULE 40A WITHOUT INTERF.  
 SITOP DC USV MODULE 24 V/40 A UNINTERRUPTIBLE POWER  
 SUPPLY WITHOUT INTERFACE INPUT: 24 V DC/43 A OUTPUT:  
 24 V DC/40 A



Input	
Supply voltage at DC Rated value	24 V
Voltage curve at input	DC
input voltage range	22 ... 29 V DC
Mains buffering	
Type of energy storage	with batteries
Charging current	
• 1	1 A
• 2	2 A
Output	
Output voltage	
• in normal operation at DC Rated value	24 V
• in buffering mode at DC Rated value	24 V
Formula for output voltage	$V_{in} - \text{approx. } 0.5 \text{ V}$
ON-delay time typical	1 s
Voltage increase time of the output voltage typical	360 ms
Output current Rated value	40 A
Active power supplied typical	960 W

Efficiency	
Efficiency in percent	
<ul style="list-style-type: none"> <li>• at rated output current at rated output current typical</li> </ul>	97.2 %
<ul style="list-style-type: none"> <li>• in case of accumulator operation typical</li> </ul>	96.9 %
Active power loss	
<ul style="list-style-type: none"> <li>• at rated output current at rated output current typical</li> </ul>	28.6 W
<ul style="list-style-type: none"> <li>• in case of accumulator operation typical</li> </ul>	33.6 W
Protection and monitoring	
Product function	
<ul style="list-style-type: none"> <li>• reverse polarity protection against energy storage unit polarity reversal</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• reverse polarity protection against input voltage polarity reversal</li> </ul>	Yes
Signaling	
Display version	
<ul style="list-style-type: none"> <li>• for normal operation</li> </ul>	Normal operation: LED green (OK), floating changeover contact "Bat/OK" to setting "OK" ("OK" means: Voltage of the supplying power supply unit is greater than cut-in threshold set at the DC UPS module); Lack of buffer standby: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Battery replacement required: LED red (alarm) flashing with approx. 0.25 Hz, floating changeover contact "Alarm/Bat" switching with approx. 0.25 Hz; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed; Permissible contact current capacity: DC 60 V/1 A or AC 30 V /1 A
<ul style="list-style-type: none"> <li>• in buffering mode</li> </ul>	Buffered mode: LED yellow (Bat), floating changeover contact "OK/Bat" to setting "Bat"; Prewarning battery voltage < 20.4 VDC: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed
Interface	
Product component PC interface	No
Design of the interface	without
Safety	
Galvanic isolation between entrance and outlet	No
Operating resource protection class	Class III
Certificate of suitability	
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• UL approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• as approval for USA</li> </ul>	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
<ul style="list-style-type: none"> <li>• relating to ATEX</li> </ul>	-

• C-Tick	No
Shipbuilding approval	-
Protection class IP	IP20

## EMC

Standard	
• for emitted interference	EN 55022 Class B
• for interference immunity	EN 61000-6-2

## Operating data

Ambient temperature	
• during operation	-25 ... +60 °C
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Environmental category acc. to IEC 60721	Climate class 3K3, no condensation

## Mechanics

Type of electrical connection	screw-type terminals
• at input	24 V DC: 2 screw terminals for 0.33 ... 10 mm <sup>2</sup> /22 ... 7 AWG
• at output	24 V DC: 2 screw terminals for 0.33 ... 10 mm <sup>2</sup> /22 ... 7 AWG
• for battery module	24 V DC: 2 screw terminals for 0.33 ... 10 mm <sup>2</sup> /22 ... 7 AWG
• for control circuit and status message	10 screw terminals for 0.5 ... 2.5 mm <sup>2</sup> /20 ... 13 AWG
Width of the enclosure	102 mm
Height of the enclosure	125 mm
Depth of the enclosure	125 mm
Required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
Net weight	1.1 kg
Product property of the enclosure housing for side-by-side mounting	Yes
Mounting type	Snaps onto DIN rail EN 60715 35x7.5/15
Electrical accessories	Battery module
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)