



Isopropyl Alcohol (IPA) - 99.8%

1610

Flux removers (defluxers) remove flux residues and other contaminants left by manufacture, rework, or repair of printed circuit boards. Residues from higher, leadfree temperatures are more baked on and harder to clean. Techspray flux removers have been proven very effective at removing fluxes baked on at leadfree temperatures.



[Request More Info](#)



99.8% pure isopropyl alcohol

99.8% pure anhydrous (containing the least water possible and no denaturant) isopropyl alcohol is excellent for tape head cleaning, defluxing, stencil cleaning, other light cleaning, and as a flux thinner. Avoid "bargain" alcohols for critical electronic cleaning. Cheap alcohols contain much more water, which slows drying and can cause oxidation, while "denatured" alcohols leave residues.

- 99.8% pure IPA
- Non-ozone depleting
- Ideal for electronics cleaning & flux thinning
- ACS reagent grade, fed spec TT-1-735A (amend 3, notice 2) grades A&B, ASTM D770-05

Specifications:

- ACS Reagent Grade IPA
- ASTM D770-05
- Fed Spec TT-1-735A

Product Packaging

1610-P
Isopropyl Alcohol
1 pt
12 units/case



1610-PT
Isopropyl Alcohol
1 pt
12 units/case



1610-G1
Isopropyl Alcohol
1 gal
1 units/case



1610-G4
Isopropyl Alcohol
1 gal
4 units/case





1610-5G
Isopropyl Alcohol
32 lbs
1 units/case



1610-54G
Isopropyl Alcohol
340 lbs
1 units/case



Technical Information

Chemical Composition

CHEMICAL NAME	CAS #
2-Propanol	67-63-0

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
Email: tsales@techspray.com

Europe

ITW Contamination Control
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
Email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

© 2017 Techspray, A Division of ITW



Techspray
8125 Cobb Center Drive,
Kennesaw, GA 30152
800-858-4043 • www.techspray.com

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 12/20/2002
MSDS No: MS1610Bulk
Date Revised: 03/02/2012
Revision No: 8

Isopropyl Alcohol**1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: Isopropyl Alcohol
GENERAL USE: General Purpose Cleaning
PRODUCT DESCRIPTION: Alcohol
PRODUCT CODE: 1610/CAN/EUR-GS, G1, G4, G, 5G, 54G
ACTIVE INGREDIENT(S): 2-Propanol

MANUFACTURER

Techspray, L.P.
 1001 N.W. 1st Street
 P.O. Box 949
 Amarillo, TX 79107

Emergency Contact: Chemtrec
Emergency Phone: 1-800-858-4043
Service Number: 1-800-858-4043

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC CCN#21858 (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666
Emergency Phone :(800) 858 - 4043

COMMENTS: This MSDS was reviewed on 30 Oct. 2006.

2. HAZARDS IDENTIFICATION**HAZARD DESIGNATION**

"F" - Highly flammable
 R11 - Highly flammable.
 "Xi" - Irritant
 R36/38 - Irritating to eyes and skin.
 "N" - Dangerous for the environment
 R52 - Harmful to aquatic organisms.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear, Colorless, Volatile Liquid

IMMEDIATE CONCERNS: Flammable liquid and vapor.

POTENTIAL HEALTH EFFECTS

EYES: Moderately irritating to the eyes.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

SKIN ABSORPTION: Skin absorption can occur.

INGESTION: This product is toxic by ingestion. Ingestion may cause irritation of the digestive tract. Nausea and vomiting will most likely occur.

INHALATION: High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and possibly death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

3. COMPOSITION / INFORMATION ON INGREDIENTS

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 12/20/2002
MSDS No: MS1610Bulk
Date Revised: 03/02/2012
Revision No: 8

Isopropyl Alcohol

Chemical Name	Wt. %	CAS	EINECS
2-Propanol	99.6 - 100	67-63-0	200-661-7

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: Do not induce vomiting. Give milk or water. Get immediate medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 11.7°C (53°F) TAG CC

FLAMMABLE LIMITS: 2.0 to 12.0

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes and oxides of carbon.

EXPLOSION HAZARDS: Vapors, when present in the flammable range (listed above), especially in a confined or poorly ventilated space, can be ignited with a flame or high intensity source of heat.

FIRE FIGHTING PROCEDURES: Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth, gravel, etc. as necessary and place in closed containers for disposal.

SPECIAL PROTECTIVE EQUIPMENT: Only personnel equipped with proper respiratory and skin/eye protection should be permitted in area. See Section 8 for details.

COMMENTS: Remove all sources of ignition. Use spark-proof tools.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use spark proof tools and explosion proof equipment.

HANDLING: Ground and bond containers when transferring material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 12/20/2002
 MSDS No: MS1610Bulk
 Date Revised: 03/02/2012
 Revision No: 8

Isopropyl Alcohol**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)										
				EXPOSURE LIMITS						
				OSHA PEL		ACGIH TLV		Supplier OEL		
Chemical Name				ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	
2-Propanol				TWA	400 ppm	980 mg/m ³	400 ppm	983 mg/m ³	NL [1]	NL [1]
				STEL	500 ppm	1225 mg/m ³	500 ppm	1230 mg/m ³	NL	NL
OSHA TABLE COMMENTS:										
1. NL = Not Listed										

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Viton, Solvex, Butyl, Buna, Neoprene.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Boiling Point (°C)	Specific Gravity
2-Propanol	11.7	82.4	0.785

PHYSICAL STATE: Liquid

ODOR: Alcohol odor

APPEARANCE: Clear, Colorless liquid

pH: Neutral

PERCENT VOLATILE: 100

VAPOR PRESSURE: 33 mmHg at 20°C

VAPOR DENSITY: 2.07 (Air=1)

BOILING POINT: to 82°C (180°F)

FREEZING POINT: to -88°C

FLASHPOINT AND METHOD: 11.7°C (53°F) TAG CC

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 12/20/2002
MSDS No: MS1610Bulk
Date Revised: 03/02/2012
Revision No: 8

Isopropyl Alcohol

SOLUBILITY IN WATER: Miscible
EVAPORATION RATE: to 1.7 (n-Butyl Acetate=1)
SPECIFIC GRAVITY: to 0.7850 (water=1)
MOLECULAR WEIGHT: 60.09 **Formula:** C₃H₈O
(VOC): 787.000 g/L (non-exempt VOC)

10. STABILITY AND REACTIVITY

STABLE: Yes
HAZARDOUS POLYMERIZATION: No
STABILITY: Stable under normal conditions.
POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: Heat, flames, ignition sources, and incompatibles.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon (CO and CO₂) may form when heated to decomposition.
INCOMPATIBLE MATERIALS: Strong acids and alkalis, reactive metals and strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION**ACUTE****DERMAL LD₅₀:** 12800 mg/kg (rabbit)**ORAL LD₅₀:** 5045 mg/kg (rat)**INHALATION LC₅₀:** 16000 ppm, 8-hour**EYE EFFECTS:** Draize test, rabbit, eye: 100 mg Severe; Draize test, rabbit, eye: 10 mg Moderate**SKIN EFFECTS:** Draize test, rabbit, skin: 500 mg Mild.**CARCINOGENICITY**

Chemical Name	NTP Status	IARC Status	OSHA Status
2-Propanol	NOT LISTED	NOT LISTED	NOT LISTED

IARC: NOT listed**NTP:** NOT listed**OSHA:** NOT listed**TERATOGENIC EFFECTS:** Test results indicate this compound/mixture is not teratogenic.**12. ECOLOGICAL INFORMATION**

ECOTOXICOLOGICAL INFORMATION: Isopropyl alcohol has a high biochemical oxygen demand and a potential to cause oxygen depletion in aqueous systems, a low potential to affect aquatic organisms, a low potential to affect secondary waste treatment microbial metabolism, a low potential to affect the germination of some plants, a high potential to biodegrade (low persistence) with unacclimated microorganisms from activated sludge.

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 12/20/2002
MSDS No: MS1610Bulk
Date Revised: 03/02/2012
Revision No: 8

Isopropyl Alcohol**13. DISPOSAL CONSIDERATIONS**

DISPOSAL METHOD: Federal, State, and Local laws governing disposal of materials can differ. Ensure compliance with proper authorities before disposal.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)****PROPER SHIPPING NAME:** ISOPROPANOL**PRIMARY HAZARD CLASS/DIVISION:** 3**UN/NA NUMBER:** UN1219**PACKING GROUP:** II**ROAD AND RAIL (ADR/RID)****KEMLER NUMBER:** UN1219**HAZARD CLASS:** 3**AIR (ICAO/IATA)****SHIPPING NAME:** ISOPROPANOL**UN/NA NUMBER:** UN1219**PRIMARY HAZARD CLASS/DIVISION:** 3**PACKING GROUP:** II**VESSEL (IMO/IMDG)****SHIPPING NAME:** ISOPROPANOL**UN/NA NUMBER:** UN1219**PRIMARY HAZARD CLASS/DIVISION:** 3**PACKING GROUP:** II**NOTE:** Page 3244**CANADA TRANSPORT OF DANGEROUS GOODS****SHIPPING NAME:** ISOPROPANOL**UN/NA NUMBER:** UN1219**PRIMARY HAZARD CLASS/DIVISION:** 3**TDG NOTE:** FLASHPOINT 12 C**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****FIRE:** Yes **ACUTE:** Yes **CHRONIC:** Yes**313 REPORTABLE INGREDIENTS:** 2-propanol (CAS #67-63-0)

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 12/20/2002
MSDS No: MS1610Bulk
Date Revised: 03/02/2012
Revision No: 8

Isopropyl Alcohol**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS
2-Propanol	99.6 - 100	67-63-0

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
2-Propanol	67-63-0

TSCA REGULATORY: All chemicals in this product are listed on the TSCA Inventory.

CANADA

WHMIS CLASS: Class B2 - Flammable Liquids. Class D2B - Toxic Materials.

CANADA INGREDIENT DISCLOSURE LIST: CAS# 67-63-0 is listed on Canada's Ingredient Disclosure List.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are listed on the Canadian DSL.

EUROPEAN COMMUNITY**EEC LABEL SYMBOL AND CLASSIFICATION**

"F" - Highly flammable
 R11 - Highly flammable.



"Xi" - Irritant
 R36/38 - Irritating to eyes and skin.



"N" - Dangerous for the environment
 R52 - Harmful to aquatic organisms.

16. OTHER INFORMATION


APPROVED BY: Pierce A. Pillon **TITLE:** Chemist

PREPARED BY: Steve Cook

REVISION SUMMARY: This MSDS replaces the 12/17/2009 MSDS.

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY	<input type="checkbox"/>	3
PHYSICAL HAZARD	<input type="checkbox"/>	1
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES

DATA SOURCES: Code of Federal Regulations (CFR) The Sigma-Aldrich Library of Regulatory and Safety Data
 OSHA Hazard Communication Standard (29CFR1910.1200) Various Federal, State and Local Regulations

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 12/20/2002
MSDS No: MS1610Bulk
Date Revised: 03/02/2012
Revision No: 8

Isopropyl Alcohol

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither Tech Spray, L.P., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.