- 1- -- 1 -- - 1 -- -1

Technical data	
General specifications	
Approvals	CE, cULus
Indicators/operating means	
LED red/green	Off: battery not detected / battery defective Red: battery is charging Green: battery is fully charged
Input	
Input voltage	100 V AC 60 Hz
Input current	approx. 0.2 mA
Output	
Output rated operating current	400 1200 mA
Output voltage	5 V DC pulsing
Mechanical specifications	
Connection	power plug for use in USA
Mass	136 g
Dimensions	230 mm x 86 mm x 51 mm

ODZ-MAH-CHARGER-UM-110V

CE **د(ال**ا US

Model Number

ODZ-MAH-CHARGER-UM-110V

Charging tray for ODZ-MAH-GRIP2/ GRIP3

Features

• For use in North and South America

Function

With the charger ODZ-MAH-CHARGER-UM-110V, you can charge the batteries of the handles ODZ-MAH-GRIP2 and ODZ-MAH-GRIP3. The RFID or barcode imager could be connected to the handle but this isn't required. It comes with a weighted base for easy table top use and a 110 V charger for use in the United States, Canada, and Mexico.

Subject to modifications without notice Pepperl+Fuchs Group www.pepperl-fuchs.com fa-info

USA: +1 330 486 0001 fa-info@us.pepperl-fuchs.com **PEPPERL+FUCHS** SENSING YOUR NEEDS

1