

Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power-over-Ethernet switch conforms to IEEE 802.3at. Includes four PoE+ ports and one standard RJ45 port, all with 10/100 Mbps speeds.

Product Features

- Auto negotiation
- Autocrossing
- Wide -40° ... +75°C temperature range
- Redundant power supply
- Automatic detection of IEEE 802.3at or 802.3af powered devices
- Wide-range power supply of 18 ... 57 V AC/DC
- POE status LED per port



Ethernet

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	900.0 GRM
Custom tariff number	85176200
Country of origin	Taiwan

Technical data

Dimensions

Width	55 mm
Height	117 mm
Depth	78 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

Technical data

Ambient conditions

Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	86 kPa ... 108 kPa (1500 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)

Interfaces

Interface 1	Ethernet
No. of ports	5 (4x POE ports, 1x 10/100 port)
Connection method	RJ45 socket
Transmission physics	Ethernet RJ45
Transmission speed	10/100 Mbps
Transmission length	100 m (Between transmitter / receiver)
Signal LEDs	LNK/ACT, 100, POE

Function

Basic functions	PSE, complies with IEEE 802.3at
Status and diagnostic indicators	LEDs: U _{S1} , U _{S2} (redundant voltage supply); alarm; LNK/ACT, POE, 100 Mbps per port
Signal contact control voltage	250 V AC
Signal contact control current	1 A

Network expansion parameters

Maximum conductor length (twisted pair)	100 m
---	-------

Supply voltage

Supply voltage	24 V DC
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Supply voltage range	18 V DC ... 57 V DC
Typical current consumption	2.7 A (48 V DC)
	2.3 A (57 V DC)
Inrush surge current	18 A (57 V DC for 100 µs)

General

Mounting type	DIN rail
Type AX	Stand-alone
Weight	685 g
Housing material	Aluminum

Mechanical tests

Type of test	Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6
Test result	5g, 150 Hz, Criterion 3

Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

Technical data

Mechanical tests

Type of test	Shock in acc. with EN 60068-2-27/IEC 60068-2-27
Test result	25g, 11 ms half-sine shock pulse

Conformity with EMC directives

Developed in acc. with standard	IEC 61000-6.2
Test standard	IEC 61000-4-2 (ESD)
Test result	Criterion B
Test standard	IEC 61000-4-3 (immunity to radiated interference)
Test result	Criterion A
Test standard	IEC 61000-4-4 (burst)
Test result	Criterion B
Test standard	IEC 61000-4-5 (surge)
Test result	Criterion B
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	Criterion A
Test standard	IEC 61000-4-8 (immunity to magnetic fields)
Test result	Criterion A
Test standard	EN 55022 (emitted interference)
Test result	Criterion A

Classifications

eCl@ss

eCl@ss 4.0	24010504
eCl@ss 4.1	24010504
eCl@ss 5.0	19030117
eCl@ss 5.1	19030117
eCl@ss 6.0	19170106
eCl@ss 7.0	19170106
eCl@ss 8.0	19170106

ETIM

ETIM 3.0	EC000734
ETIM 4.0	EC000734
ETIM 5.0	EC000734

UNSPSC

UNSPSC 6.01	43172015
-------------	----------

Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

Classifications

UNSPSC

UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201410
UNSPSC 13.2	43201410

Accessories

Accessories

End block

End clamp - E/NS 35 N - 0800886



End clamp, width: 9.5 mm, color: gray

Patch cable

Patch cable - FL CAT5 PATCH 0,3 - 2832250



Patch cable, CAT5, assembled, 0.3 m

Patch cable - FL CAT5 PATCH 0,5 - 2832263



Patch cable, CAT5, assembled, 0.5 m

Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

Accessories

Patch cable - FL CAT5 PATCH 1,0 - 2832276



Patch cable, CAT5, assembled, 1.0 m

Patch cable - FL CAT5 PATCH 1,5 - 2832221



Patch cable, CAT5, assembled, 1.5 m

Patch cable - FL CAT5 PATCH 2,0 - 2832289



Patch cable, CAT5, assembled, 2.0 m

Patch cable - FL CAT5 PATCH 3,0 - 2832292



Patch cable, CAT5, assembled, 3.0 m

Patch cable - FL CAT5 PATCH 5,0 - 2832580



Patch cable, CAT5, assembled, 5.0 m

Industrial Ethernet Switch - FL SWITCH 1001T-4POE - 2891064

Accessories

Patch cable - FL CAT5 PATCH 7,5 - 2832616



Patch cable, CAT5, assembled, 7.5 m

Patch cable - FL CAT5 PATCH 10,0 - 2832629



Patch cable, CAT5, assembled, 10.0 m
