


# Keysight Technologies

N2790A 100 MHz, N2791A 25 MHz and  
N2891A 70 MHz High-voltage Differential  
Probes

Data Sheet

## Introduction

Oscilloscope users often need to make floating measurements where neither point of the measurement is at earth ground. Use the N2790A, N2791A or N2891A high-voltage differential probe to make safe and accurate floating measurements with an oscilloscope. The N2790A, N2791A and N2891A high-voltage differential probes allow conventional earth-grounded Keysight Technologies, Inc. oscilloscopes to be used for floating signal measurements.



## Table of Contents

|                                  |    |
|----------------------------------|----|
| Introduction.....                | 02 |
| Performance Characteristics..... | 08 |
| Ordering Information .....       | 09 |
| Keysight Oscilloscopes .....     | 10 |



With a differential amplifier in the probe head, the N2790A is rated to measure differential voltage up to 1,400 VDC + peak AC with high CMRR (common mode rejection ratio) of > 50 dB at 1 MHz. The N2791A and N2891A can measure differential voltage up to 700 V and 7 kV differential or common mode respectively. The N2790A, N2791A and N2891A differential probe offers sufficient dynamic range and bandwidth for your application to make the floating measurements found in power electronics circuits safely and accurately.

The N2790A, N2791A and N2891A differential probe offers user selectable attenuation settings that make it highly versatile, allowing it to be used for a broad range of applications. The probe comes with probe tip accessories for use with both small or large components in tight places. The N2790A and N2891A also have an overrange indicator which alerts the user when the probe input exceeds the dynamic range of the probe.

The N2791A and N2891A are compatible with any oscilloscope with 1 Mohm BNC input. The N2791A and N2891A probe's power is supplied by included 4x AA batteries or USB host port of the scope or PC via a supplied USB power cable. The N2790A is compatible with the Keysight Technologies, Inc. AutoProbe interface where the probe's power is supplied by the Keysight oscilloscope's probe interface.



Figure 2. N2791A 25-MHz high-voltage differential probe with standard accessories.




Figure 3. N2891A 70-MHz high-voltage differential probe with standard accessories.




Figure 1. N2790A high voltage differential probe with standard accessories.

| Keysight oscilloscope compatibility  | Max number of N2790A probes supported by oscilloscope |
|--|---|
| InfiniiVision 5000, 6000 (except 100 MHz), and 7000 Series with version 5.26.0001 software | 4   |
| InfiniiVision 3000 X- and 4000 X-Series  | 4   |
| Infiniiium 8000, 54830 Series with version 5.7 software                                    | 4   |
| Infiniiium 9000 Series with version 2.0 software   | 4   |






Figure 4.  $V_{out}/V_{in}$  vs. frequency response of N2790A.




Figure 5. Frequency response ( $V_{out}/V_{in}$ ) of N2790A when inputs are driven in common (common mode rejection).




Figure 6. Input impedance vs. frequency of N2790A.






Figure 7. Voltage derating curve of N2790A (voltage between either input and ground).




Figure 8. V<sub>out</sub>/V<sub>in</sub> vs. frequency response of N2791A.




Figure 9. Frequency response (V<sub>out</sub>/V<sub>in</sub>) of N2791A when inputs are driven in common (common mode rejection).






Figure 10. Input impedance vs. frequency of N2791A.




Figure 11. Voltage derating curve of N2791A (voltage between either input and ground).






Figure 12.  $V_{out}/V_{in}$  vs. Frequency response of N2891A at 1000:1 attenuation.




Figure 13. Frequency response ( $V_{out}/V_{in}$ ) of N2891A when inputs are driven in common (common mode rejection).








Figure 14. Input impedance vs. Frequency of N2891A.




Figure 15. Voltage derating curve of N2891A (voltage between either input and ground).





## Performance Characteristics

| Product number  | N2790A   | N2791A  | N2891A   |
|---|--|---|--|
| Bandwidth (-3 dB)                                     | ≥ 100 MHz probe bandwidth <sup>1</sup>   | ≥ 25 MHz probe bandwidth  | ≥ 70 MHz   |
| Rise time (calculated)                                | ≤ 3.5 ns   | ≤ 14 ns   | ≤ 5 nsec   |
| Attenuation   | 50:1/500:1   | 10:1/100:1  | 100:1/1000:1   |
| Gain accuracy (% of reading)                          | ± 2% at 20 to 30 °C<br>± 4% at 0 to 20 °C and 30 to 50 °C <sup>1</sup>   |   |  |
| DC CMRR   | -70 dB at 500 VDC  |   |  |
| AC CMRR   | -80 dB at 50/60 Hz<br>-50 dB at 1 kHz<br>-50 dB at 1 MHz   | -80 dB at 50/60 Hz<br>-40 dB at 1MHz  | -80 dB at 50/60 Hz<br>-60 dB at 20 kHz   |
| Propagation delay                                     | 14 nsec at 50:1<br>2.8 nsec at 500:1   |   |  |
| Input R//C (each input to ground)                     | 4 Mohm // 7 pF   | 4 Mohm // 10 pF   | 50 Mohm // 7 pF  |
| Input R//C (between inputs)                           | 8 Mohm // 3.5 pF   | 8 Mohm // 8 pF  | 100 Mohm // 5 pF   |
| Max differential operating voltage (DC+PeakAC or RMS) | ± 1400 V at 500:1<br>± 140 V at 50:1   | ± 700 V at 100:1<br>± 70 V at 10:1  | ± 7000 V or 5000 Vrms at 1000:1<br>± 700 V or 700 Vrms at 100:1  |
| Max common mode operating voltage (DC+PeakAC or RMS)  | ± 1000 V (CAT II)<br>± 600 V (CAT III)   | ± 700 V at 100:1<br>± 700 V at 10:1   | ± 7000 V or 5000 Vrms at 1000:1<br>± 7000 V or 5000 Vrms at 100:1  |
| Max nondestructive voltage                            | ± 1500 VDC + Peak AC differential mode<br>± 1300 Vrms (CAT II) common mode   | ± 1000 Vrms (CAT II) differential and common mode   | ± 7000 V (DC + Peak AC)<br>± 5000 Vrms at 1000:1 and 100:1 in differential and common mode (Main Isolated)   |
| Output maximum voltage range                          | ± 2.8 V into 1 Mohm (500:1)  | 7 V into 1 Mohm (100:1)   | 7 V into 1 Mohm (1000:1)   |
| Scope's input impedance                               | 1 Mohm AutoProbe interface   | 1 Mohm BNC interface  | 1 Mohm BNC interface   |
| Output offset   | Adjustable   | ± 7.5 mV (typical)  | ± 5 mV (typical)   |
| Noise referenced to input                             | < 300 mVrms at 500:1<br>< 50 mVrms at 50:1   |   |  |
| Temperature - operating                               | -10 to 50 °C   | -10 to 40 °C  | -10 to 40 °C   |
| Temperature - non-operating                           | -51 to 71 °C   | -30 to 71 °C  | -30 to 71 °C   |
| Humidity - operating                                  | 80% RH at 40 °C  | 25 to 85% RH  | 25 to 85% RH   |
| Humidity - non-operating                              | 90% RH at 65 °C  | 25 to 85% RH  | 25 to 85% RH   |
| Operating altitude                                    | 2,000 m  | 3,000 m   | 3,000 m  |
| Nonoperating altitude                                 | 15,300 m   | 15,300 m  | 15,300 m   |
| Vibration   | Keysight class GP and MIL-PRF-28800F class 3 random  |   |  |
| Shock   | Tip end: 400g 1/2 sine wave<br>AutoProbe BNC End: 50g 1/2 sine wave<br>Probe circuit box: Keysight class B1 and MIL-PRF-28800F class 3   |   |  |
| Standard accessories                                  | 2 each browser tips (black and red)<br>2 each alligator plunger clips (black and red)<br>2 each pincer clips (black and red)<br>2 each of 4 colored ID tags<br>DC offset adjustment tool<br>Manual | 2 each alligator clips (black and red)<br>2 each hook clips (black and red)<br>USB power cord (2 m)<br>4 AA batteries<br>Manual | 2 each high-voltage alligator clips (black and red)<br>2 each safety hook adapters (black and red)<br>USB power cord (2 m)<br>4 AA batteries<br>Manual |
| Safety specifications                                 | IEC61010-031   | IEC61010-031  | IEC61010-031   |

1. Denotes warranted specification after 20 minute warm-up, all others are typical.



When probing differential signals inside of environmental chambers at extreme temperatures, Keysight offers the N7013A extreme temperature extension kit shown in Figure 16. The N7013A is compatible with the N2790A and N2791A differential probes at de-rated bandwidths. The 70 cm long differential cable set and accessories can operate in temperatures ranging from -40 degrees to +85 degree Celsius. Although the N7013A is also mechanically compatible with the N2891A differential probe, de-rated bandwidths are not available and specifications are not guaranteed.



Figure 15. Versatile probe tip accessories allow you to access small or large components in tight places.





Figure 16. The N7013A extreme temperature probing kit for differential probes.

## Ordering Information

| Product number | Description   |
|----------------|---|
| N2790A         | 100 MHz high-voltage differential probe   |
| N2790-68700    | Probe tip accessory kit for N2790A including 2 each of browser tips, alligator plunger clips and pincer clips |
| N2791A         | 25-MHz high-voltage differential probe  |
| N2791-68700    | Probe tip accessory kit for N2791A including 2 alligator clips and 2 hook clips                               |
| N2891A         | 70-MHz high-voltage differential probe  |
| N2891-68700    | Probe tip accessory kit for N2891A including 2 high-voltage alligator clips and 2 safety hook adapters        |
| 0960-2926      | CAN/FlexRay DB9 probe head for N2790A/91A/92A differential probe  |
| N7013A         | Extreme temperature probe kit for the N2790 and N2791A  |
| N7014A         | Banana-to-socketed adapters (1 pair)  |





## Keysight Oscilloscopes

Multiple form factors from 20 MHz to > 90 GHz | Industry leading specs | Powerful applications





[www.axistandard.org](http://www.axistandard.org)

AdvancedTCA® Extensions for Instrumentation and Test (AXIe) is an open standard that extends the AdvancedTCA for general purpose and semiconductor test. The business that became Keysight was a founding member of the AXIe consortium. ATCA®, AdvancedTCA®, and the ATCA logo are registered US trademarks of the PCI Industrial Computer Manufacturers Group.



[www.lxistandard.org](http://www.lxistandard.org)

LAN eXtensions for Instruments puts the power of Ethernet and the Web inside your test systems. The business that became Keysight was a founding member of the LXI consortium.



[www.pxisa.org](http://www.pxisa.org)

PCI eXtensions for Instrumentation (PXI) modular instrumentation delivers a rugged, PC-based high-performance measurement and automation system.

## Download your next insight

Keysight software is downloadable expertise. From first simulation through first customer shipment, we deliver the tools your team needs to accelerate from data to information to actionable insight.

- Electronic design automation (EDA) software
- Application software
- Programming environments
- Productivity software



Learn more at

[www.keysight.com/find/software](http://www.keysight.com/find/software)

Start with a 30-day free trial.


[www.keysight.com/find/free\\_trials](http://www.keysight.com/find/free_trials)



## Evolving Since 1939

Our unique combination of hardware, software, services, and people can help you reach your next breakthrough. We are unlocking the future of technology.

From Hewlett-Packard to Agilent to Keysight.



### myKeysight

myKeysight

[www.keysight.com/find/mykeysight](http://www.keysight.com/find/mykeysight)

A personalized view into the information most relevant to you.

[http://www.keysight.com/find/emt\\_product\\_registration](http://www.keysight.com/find/emt_product_registration)

Register your products to get up-to-date product information and find warranty information.

### KEYSIGHT SERVICES

Accelerate Technology Adoption.  
Lower costs.

Keysight Services

[www.keysight.com/find/service](http://www.keysight.com/find/service)

Keysight Services can help from acquisition to renewal across your instrument's lifecycle. Our comprehensive service offerings—one-stop calibration, repair, asset management, technology refresh, consulting, training and more—helps you improve product quality and lower costs.



Keysight Assurance Plans

[www.keysight.com/find/AssurancePlans](http://www.keysight.com/find/AssurancePlans)

Up to ten years of protection and no budgetary surprises to ensure your instruments are operating to specification, so you can rely on accurate measurements.

Keysight Channel Partners

[www.keysight.com/find/channelpartners](http://www.keysight.com/find/channelpartners)

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

[www.keysight.com/find/probes](http://www.keysight.com/find/probes)

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at:

[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

### Americas

|               |                  |
|---------------|------------------|
| Canada        | (877) 894 4414   |
| Brazil        | 55 11 3351 7010  |
| Mexico        | 001 800 254 2440 |
| United States | (800) 829 4444   |

### Asia Pacific

|                    |                |
|--------------------|----------------|
| Australia          | 1 800 629 485  |
| China              | 800 810 0189   |
| Hong Kong          | 800 938 693    |
| India              | 1 800 11 2626  |
| Japan              | 0120 (421) 345 |
| Korea              | 080 769 0800   |
| Malaysia           | 1 800 888 848  |
| Singapore          | 1 800 375 8100 |
| Taiwan             | 0800 047 866   |
| Other AP Countries | (65) 6375 8100 |

### Europe & Middle East

|                |               |
|----------------|---------------|
| Austria        | 0800 001122   |
| Belgium        | 0800 58580    |
| Finland        | 0800 523252   |
| France         | 0805 980333   |
| Germany        | 0800 6270999  |
| Ireland        | 1800 832700   |
| Israel         | 1 809 343051  |
| Italy          | 800 599100    |
| Luxembourg     | +32 800 58580 |
| Netherlands    | 0800 0233200  |
| Russia         | 8800 5009286  |
| Spain          | 800 000154    |
| Sweden         | 0200 882255   |
| Switzerland    | 0800 805353   |
|                | Opt. 1 (DE)   |
|                | Opt. 2 (FR)   |
|                | Opt. 3 (IT)   |
| United Kingdom | 0800 0260637  |

For other unlisted countries:

[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)  
(BP-9-7-17)

DEKRA Certified  
ISO 9001 Quality Management System

[www.keysight.com/go/quality](http://www.keysight.com/go/quality)

Keysight Technologies, Inc.  
DEKRA Certified ISO 9001:2015  
Quality Management System

This information is subject to change without notice.

© Keysight Technologies, 2018  
Published in USA, April 11, 2018  
5990-3780EN

[www.keysight.com](http://www.keysight.com)

