



## 780 HANDHELD TEST INSTRUMENT

The 780 Handheld Test Instrument is a portable multimedia generator and analyzer that enables you to conduct quick verification tests of all your HDMI® Products—source, sinks, repeaters, distribution devices—on-site or in an R&D environment. The instruments' color touch displays make them easy and convenient to use.

The 780 Test Instrument supports pixel rates up to 165MHz and TMDS clock rates up to 225MHz for deep color on the HDMI Tx port and up to 150MHz on the HDMI Rx port.

### TESTING HDMI SINK DEVICES

The 780 is equipped with an HDMI output port for testing HDMI sink devices. You can test and calibrate the video on your high definition TVs with a variety of resolutions and standard 2D or 3D test patterns as well as custom patterns from THX® and ISF®. You can also verify hot plug, EDID and HDCP and CEC messaging on HDMI sink devices.

### ANALYZING HDMI SOURCE DEVICES

The 780 is also equipped with an HDMI input port for verifying HDMI source devices. The HDMI input port and built-in display enable you to verify the incoming video parameters and view the entire, unscaled video image—including 4K images by panning, even when encrypted with HDCP. You can also verify the incoming audio by examining the decoded IEC audio headers, audio infoframes and channel status blocks.

### TESTING HDMI CABLES & DISTRIBUTION NETWORKS

Because the 780 has both an HDMI output and an HDMI input, you can test your HDMI cables and distribution systems (splitters, extenders and switches) with the Cable Test feature. You can prequalify cables and distribution systems prior to installation or once they are installed with the Frame Compare (Pixel Error) test feature.

### MONITORING HDMI PROTOCOLS

With the Auxiliary Channel Analyzer (ACA) options, you can monitor the HDMI hot plug related events and DDC transactions, EDID and HDCP, between HDMI devices and the 780 while the 780 is emulating a known-good HDMI source or sink device. The second ACA option enables you to passively monitor the HDMI hot plug-related events and DDC transactions on three HDMI connected devices.



(Note: Above image shown with optional 4-port board to support ACA passive monitoring.)

## KEY FEATURES + BENEFITS

**HDMI Output Port - Pattern Testing including 3D and Deep Color**  
Up to 225MHz with 24/30/36 bit color depths at 1080p60.

**HDMI Input Port - Analysis of HDMI sources**  
Up to 150MHz at 1080p60.

**HDMI 3D Pattern Generation**  
Test Side-by-Side, Top/Bottom and Frame Packing 3D format structures.

**Analog Component Video Output**  
Pattern testing for analog component inputs on HDTVs.

**Custom Formats and Bitmap Patterns**  
Create custom formats using Format Editor tool. Import your bitmaps for pattern testing.

**Test Pattern Scrolling**  
Animated test pattern for testing motion artifacts.

**Licensed Bitmap Images (optional)**  
Image packs w/ bitmap test images. Current pattern packs: THX®, China Res and ISF®.

**Multichannel Digital Audio**  
Verify audio-capable devices using multichannel audio over HDMI, SPDIF, and Optical outputs with various audio formats at sampling rates up to 192kHz. Test LPCM and Dolby and DTS compressed audio formats.

**Color Touch Screen - View Incoming Video**  
User friendly color touch screen enables you to operate the instrument and view incoming video and metadata from an HDMI source. View incoming video—scaled or unscaled, encrypted or unencrypted.

**Installer Test Utility**  
Diagnose HDMI interoperability problems with simplified test interface. Verify sources, sinks, repeaters with "one button" tests. Pass/fail results provided.

**HDCP Sink Test (Network Analyzer option)**  
Verify that an HDMI display properly responds to HDCP content protection.

**HDCP Source Test (Network Analyzer option)**  
Check max HDMI devices supported by source.

**EDID Verification (Network Analyzer option)**  
Verify the HDMI display's EDID for checksum and header errors. View the display's entire EDID content. Compare two EDIDs. Run portions of the EDID compliance test.

**HDMI Sink Emulator (Network Analyzer option)**  
Emulate an HDMI sink device to test EDID on HDMI source device; test a source response to a variety of stored EDIDs. EDID.

**HDMI Source Video Testing (Network Analyzer option)**  
View the video timing data and video infoframe data from an HDMI source device including 3D metadata. View various data island packet contents.

**HDMI Source Audio Testing (Network Analyzer option)**  
Verify incoming audio (format, sampling rate, bit depth) by viewing the decoded IEC audio headers, audio infoframes and channel status bits.

**HDMI Cable & Network Test (Cable & Link test option)**  
Prequalify or verify your HDMI cable and HDMI distribution network (extenders, splitters, switches, etc) using a pseudo random noise test pattern or pixel error test with Frame Compare feature.

**Aux channel analyzer (ACA optional)**  
Monitor the CEC HDMI hot plug related events and DDC transactions, EDID and HDCP, either while emulating a known-good HDMI device or while passively monitoring between multiple HDMI connected devices.  
**Note: Passive monitoring requires optional hardware configuration.**

**Battery powered**  
Provides portability with rechargeable batteries. Can also be powered from AC through power adapter.

**Command Line Control**  
Run automated tests through command line interface via USB.

# 780 Handheld Test Instrument

**STANDARD FEATURES**

Video Pattern testing Formats	
Number of formats	147 Standards
CEA-861E; VESA Deep Color	
	1080p60 30/36 bit
<b>Patterns</b>	
Number of patterns	More than 40 patterns
Gray levels	256
Imported bitmaps	Fixed resolution 24 bit
Imageshift	Scroll bitmap images
<b>HDMI 3D Testing</b>	
Test pattern	3D bitmap test images and NEW rendered images
3D Formats	Top & Bottom, Side-by-Side (half & full), Frame Packing
<b>Audio Test Tones</b>	
<b>Test</b>	<b>Tone</b>
Sound Pressure & Main Speaker	Plnk Noise 500-2kHz
Frequency Response	20-20kHz
Speaker Distortion	Sine wave 63 Hz, 125Hz, 1kHz, 4kHz
Early Reflections	Impulse
Polarity of speaker wires	Polarity
Sound Convergence	Autotime Delay
View incoming video	
HDMI Source Test	View incoming video image and video metadata from HDMI source even when content is protected with HDCP.
<b>HDMI Installer Test Utility</b>	
<b>Type</b>	<b>Function</b>
Source Test	HDCP, video, video timing
Sink Test	Hot plug, EDID, HDCP, video, video type
Repeater Test	Hot plug, EDID, HDCP, video, video type, video timing
Link Test	Hot plug, EDID, HDCP, video, video type, video timing

**SPECIFICATIONS**

**Video/Audio Outputs**

**HDMI / DVI Video Output**

Connector type	(1) one HDMI Type A
TMDS protocols	HDMI, DVI
Number of links	single
Colorimetry	
	ITU-R BT.601-5; ITU-R BT.709-5
Color depth (HDMI)	
	24/30/36bit 4:4:4 RGB/YCbCr 16/20/24-bit 4:2:2
Color depth (DVI)	
	24-bits per pixel RGB 4:4:4
Encoding	RGB, YCbCr
Sampling modes	4:4:4; 4:2:2
Pixel rate (780)	165MHz
TMDS clock rate (780)	2.25Gb/s
Timings (780)	up to 1080p60
Scan types	Progressive, interlaced

**Analog Video - VGA & Component**

Connector type	VGA (HD15F) VGA-to-RCA adapter provided
Color encoding	RGB, YPbPr
Pixel rate (MHz)	80 (pixel rep for higher resolutions)
Sync types	Separate, composite

**HDMI Input**

Connector type	(1) one HDMI Type A
TMDS protocols	HDMI, DVI
Number of links	single
Pixel rate (780)	150MHz
Sampling modes	4:4:4; 4:2:2

**OPTIONAL FEATURES**

<b>HDMI Network Analyzer Option</b>	
HDMI Source Video Test	View the HDMI video timing data and video inframe data (including 3D metadata) from an HDMI source device.
HDMI Source Audio Test	View the audio format, sampling rate, Bit depth of the decoded audio IEC headers, audio inframes, and channel status bits of an HDMI audio source.
CEC Ping test	HDMI CEC source & sink devices Ping HDMI devices in a network to discover CEC devices.
<b>HDCP</b>	
HDMI HDCP Sink Test	Verifies DTV's and repeater's handling of HDCP encrypted video.
HDMI Source Test	Check a sources max HDCP device capabilities.
<b>EDID</b>	
HDMI EDID Sink Test	View entire EDID contents and check for errors. Run portions of the EDID compliance test.
HDMI EDID Source Test	Emulate any EDID and test a source's response. Store/Load EDIDs.

**Digital Audio (HDMI)**

Connector	(1) one HDMI Type A
Bits per sample	16, 20, 24
Sampling rates (kHz)	32.0, 44.1, 48, 88.2, 96, 176.4, 192
Audio stream types	
Programable LPCM (IEC 60958)	All sampling freq, up to 8 channel
Dolby Digital (IEC 61937)	Noise patterns, 5.1
Dolby Digital Plus (IEC 61937)	Sine wave clips 192kHz, 2.0, 5.1 & 7.1
Dolby TrueHD	High Bit Rate Audio
DTS-ES (IEC 61937)	Noise pattern 5.1
DTS-HD HRA (IEC 61937)	Sine wave clips 192kHz, 5.1 & 7.1
DTS Master Audio	High Bit Rate Audio

**Digital Audio (SPDIF, OPTICAL)**

Connector	
SPDIF	RCA
OPTICAL	JIS F0S
HDMI IN (ARC) 780A only	HDMI Type A
Bits per sample	16, 20, 24
Sampling rates (kHz)	32, 44.1, 48, 88.2, 96, 176.4, 192
Audio stream types	
Programable LPCM (IEC 60958)	All sampling freq, up to 8 channel
Dolby Digital (IEC 61937)	Noise patterns, 5.1
DTS-ES (IEC 61937)	Noise pattern 5.1

**Administration**

Firmware upgrade	In the field upgrade through USB.
------------------	-----------------------------------

**Control**

USB peripheral	Download bitmaps, firmware upgrade
Command Line	USB

**User Interface – Touch Screen**

Screen size (active)	480(H) x 272(V)
Color	24 bit RGB

**OPTIONAL FEATURES**

<b>HDMI Cable &amp; Link Test Option</b>	
HDMI Link (network) Test	Run pixel error and Frame Compare test on HDMI cable networks comprised of cables, extenders, repeaters, switches, processors, etc. Tests for pixel errors on video using pseudo random noise. Tests continuity of 5V, hot plug, CEC bus and DDC lines.
<b>Auxiliary Channel Analyzer Option</b>	
1 - Emulation Monitoring	Monitor the CEC hot plug events and the DDC transactions during a connection sequence between the 780 and another HDMI device while emulating either a known-good HDMI source device, known-good display device, or both.
2 - Passive Monitoring (includes option 1 - Emulation Monitoring)	Passively monitor the CEC 5V and hot plug events and the DDC transactions during a connection sequence between HDMI devices (source, repeater and display device).
Note: Requires an extra board with four (4) additional HDMI ports.	
<b>Image Packs Option</b>	
Image Packs	China Res Pattern Pack THX® Pattern Pack ISF® Pattern Pack

**Environmental**

Humidity	30% to 80% RH non condensing
Operating temp	
Celsius	0 to 40
Fahrenheit	32 to 104

**Regulatory**

FCC class B	
RoHS	

**Power**

DC	6AA NiMH batteries
Battery life	2 hours between charge
Battery recharge	Overnight charge
AC charger/converter	
VAC	100 to 240
Current (amps)	0.4 (max)
Frequency (Hz)	47 to 63
Power (VA)	30

**Weight**

LBS	3.25 LBS
Kg	1.47 Kg



**Size (dimensions)**

Height	
inches	2.7
cm	6.98
Width	
inches	9.75
cm	24.76
Depth	
inches	6
cm	15.24

STANDARD TESTS

**Video Pattern Testing** – Test a DTV to ensure that it can render a video test pattern. Scroll a pattern to test for motion artifacts.


**Configurations:**



**Operation:**  
Step 1. Select Format



Step 2. Select Video Pattern



Step 3. Select Image





Step 4. Select Pattern Options



**3D Video Pattern Testing** – Test a DTV to ensure that it can render a video test pattern.

**Configurations:**




**Operation:**

Step 1. Select 3D Output



Step 2. Select 3D Test Options





Step 3. Select 3D Test pattern




## Audio Test Tones – Test an HDTV or A/V Receiver to ensure that it can render LPCM basic and multichannel audio and multichannel compressed audio and HDMI high bit rate audio formats.

### Configurations:



### Operation:

#### Step 1. Select Audio Test Tones



#### Step 2. Select HDMI Audio Pattern DD+ 7.1






#### Step 3. Select Pattern Options




## Viewing HDMI Video from Source – Test an HDMI source device directly or through a repeater. View incoming HDMI video including 3D video on the built-in display.

### Configurations:




### Operation:


#### Step 1. Select Test Source (DVD/STB)




#### Step 2. Select Video Display



#### Step 3. Select Fullscreen or Detailed




#### Step 4. View incoming HDMI video on built-in display




## Installer Test Utility – Test an HDMI sink device directly.

### Configurations:




### Operation:

#### Step 1. Select Installer Test




#### Step 2. Select Sink Test



#### Step 3. Select OK



#### Step 4. View video and verify if it is correct




#### Step 5. View Results



## Installer Test Utility – Test an HDMI source device directly.

### Configurations:




### Operation:

#### Step 1. Select Installer Test




#### Step 2. Select Source Test




#### Step 3. Select OK



#### Step 4. View video and verify if it is correct




#### Step 5. View Results



## Installer Test Utility – Test an HDMI repeater device directly.

### Configurations:




### Operation:


#### Step 1. Select Installer Test




#### Step 2. Select Repeater Test



#### Step 3. Select OK




#### Step 4. View video and verify if it is correct



## Installer Test Utility – Test HDMI Links.

### Configurations:




### Operation:


#### Step 1. Select Installer Test




#### Step 2. Select Link Test



#### Step 3. Select OK





#### Step 4. View video and verify if it is correct



**HDMI NETWORK ANALYZER FEATURES (OPTIONAL)**


**HDCP Testing – Run an HDCP functional test connected directly to an HDMI HDTV or through a repeater to verify that it can render HDCP protected video content.**

**Configurations:**




**Operation:**

Step 1. Select Test Sink (DVD/STB)



Step 2. Select HDCP Test






Step 3. Select Enable and View results



**HDMI CEC Verification – Run an HDMI CEC verification test on an HDMI system.**

**Configurations:**




**Operation:**

Step 1. Select Test Sink (DVD/STB)



Step 2. Select CEC Test




Step 3. View Results



## HDMI Source and Repeater Video Test – Test an HDMI source device directly or through a repeater. Verify timing, AVI Infoframes and HDCP authentication for standard video, deep color and 3D.

### Configurations:




### Operation:

#### Step 1. Select Test Source (DVD/STB)



#### Step 2. Select Format Analyzer






#### Step 3. View Results



## HDMI Source Audio Test – Run an audio test on an HDMI source device or A/V receiver to verify audio headers, audio infoframe and channel status bits.

### Configurations:




### Operation:


#### Step 1. Select Test Source (DVD/STB)



#### Step 2. Select Audio Analyzer





#### Step 3. View Results





## Packet Viewer Test – View HDMI infoframe and selected data island metadata

### Configurations:




### Operation:

#### Step 1. Select Test Source (DVD/STB)



#### Step 2. Select Packet Viewer



#### Step 3. View Results





#### Step 4. View multiple pages



## Testing Source's Response to an EDID – Provision 780's HDMI Input port with EDID from any display. Verify source responds properly to EDID. Load EDID from multiple stored EDIDs.

### Configurations:




### Operation:

#### Step 1. Select Test Sink (DVD/STB)



#### Step 2. Select EDID Test




#### Step 3. Load EDID



#### Step 3. Load an EDID to RX port





#### Step 3. Verify EDID has been assigned



## EDID Sink Testing – Run an EDID functional test on an HDMI HDTV and/or an A/V receiver to verify EDID checksum, header, and HDMI video and audio support. View entire EDID contents. Run portions of the EDID compliance test

### Configurations:




### Operation:


#### Step 1. Select Test Sink (DVD/STB)



#### Step 2. Select EDID Test



#### Step 3. Select Read and View Results (Page 1)





#### Step 4. View multiple pages (Page 25)



## HDMI CABLE & LINK TEST (OPTIONAL)

### HDMI Cable or HDMI Link Test – Run a pixel error test on an HDMI cable or an HDMI system with splitters, switches and extenders using pseudo random noise.

### Configurations:



### Operation:


#### Step 1. Select Cable/Repeater Test



#### Step 2. Select Test Wire or Test Repeater




#### Step 3. View Results (Cable Test)



## HDMI FRAME COMPARE TEST (OPTIONAL)

HDMI Frame Compare Test – Run a pixel error test on video frames.

### Configurations:



### Operation:

#### Step 1. Select Cable/Repeater Test




#### Step 2. Select Frame Capture



#### Step 3. Select Frame Compare






#### Step 4. Select Frame Capture



## HDMI AUXILIARY CHANNEL ANALYZER TEST (EMULATION OPTION)


Emulation Monitoring – Monitor HDCP and EDID transactions and hot plug events while emulating either an HDMI source, HDMI sink or both an HDMI source and sink.

### Configurations:



### Operation:


#### Step 1. Select Aux Channel Analyzer




#### Step 2. Select Configuration: Capture Data



#### Step 3. View Results (Downstream)






#### Step 4. View Details (Bcaps)



## HDMI AUXILIARY CHANNEL ANALYZER TEST (PASSIVE OPTION)

**Passive Monitoring – Passively monitor hot plug-related events, HDCP and EDID transactions between HDMI connected devices.**



### Operation:

