




COLOR-CODED STRAIGHT STRAIN RELIEF CONDUIT AND CORD CONNECTORS

Color-Coded Straight Strain Relief Cord Connectors Steel

B58.1



TRADE SIZE		CABLE RANGE		Dim A	Dim B
37224	1/2"	BRN	3/8-20	1.44	1.12
37225	1/2"	BLU	3/8-20	1.44	1.12
37226	1/2"	GRN	3/8-20	1.44	1.12
37227	1/2"	RED	3/8-20	1.44	1.12
37228	1/2"	WHI	3/8-20	1.44	1.12
37229	3/4"	BRN	3/4-16	1.80	1.28
37230	3/4"	BLU	3/4-16	1.80	1.28
37231	3/4"	GRN	3/4-16	1.80	1.28
37232	3/4"	RED	3/4-16	1.80	1.28
37233	3/4"	WHI	3/4-16	1.80	1.28
37234	1"	BRN	1-14	2.16	1.52
37235	1"	BLU	1-14	2.16	1.52
37236	1"	GRN	1-14	2.16	1.52
37237	1"	RED	1-14	2.16	1.52
37238	1"	WHI	1-14	2.16	1.52
37239	1 1/4"	BRN	1 1/4-12	2.70	1.92
37240	1 1/4"	BLU	1 1/4-12	2.70	1.92
37241	1 1/4"	GRN	1 1/4-12	2.70	1.92
37242	1 1/4"	RED	1 1/4-12	2.70	1.92
37243	1 1/4"	WHI	1 1/4-12	2.70	1.92
37244	2"	BRN	2-10	3.24	2.24
37245	2"	BLU	2-10	3.24	2.24
37246	2"	GRN	2-10	3.24	2.24
37247	2"	RED	2-10	3.24	2.24
37248	2"	WHI	2-10	3.24	2.24
37249	2 1/2"	BRN	2 1/2-8	3.96	2.64
37250	2 1/2"	BLU	2 1/2-8	3.96	2.64
37251	2 1/2"	GRN	2 1/2-8	3.96	2.64
37252	2 1/2"	RED	2 1/2-8	3.96	2.64
37253	2 1/2"	WHI	2 1/2-8	3.96	2.64
37254	3"	BRN	3-6	4.50	2.88
37255	3"	BLU	3-6	4.50	2.88
37256	3"	GRN	3-6	4.50	2.88
37257	3"	RED	3-6	4.50	2.88
37258	3"	WHI	3-6	4.50	2.88



Catalog #: 3724-1

APPLICATIONS

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable. RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations.

PRODUCT FEATURES

- Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification
- Steel construction provides mechanical strength and durability
- Metallic components are zinc plated for corrosion protection
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal
- Time saving and easy installation - no need to disassemble the fitting for cord installation
- Male tapered thread NPT
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- N/A

CULUS

UL File E195973

NEMA

NEMA 4

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf

GENERAL PRODUCT INFORMATION

Trade Size: 1 in.
Cable Range: .55 - .65
Color Code: Brown

DRAWING DIMENSIONS

Dimension A: 1.75
Dimension B: 1.50

PACKAGING

Package Type: Carton
Ship Carton Qty.: 25
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 28.30
Ship Carton Length (in.): 6.00
Ship Carton Width (in.): 6.00
Ship Carton Height (in.): 6.00
Ctn Weight (Lbs.): 7.08
UPC Number: 050169983096
I2of5: 50050169983091