
Filter regulator MS6N-LFR-1/2-D7-CRV-AS Part number: 531288







Data sheet

Feature	Value
Size	6
Series	MS
Actuator lock	Rotary knob with lock
	with accessories, lockable
Assembly position	Vertical +/- 5°
Grade of filtration	5 μm
Condensate drain	fully automatic
Design structure	Filter regulator with pressure gauge
Max. condensate volume	38 ml
Controller function	Output pressure constant
	with secondary exhaust
Bowl guard	Plastic guard
Pressure gauge	with pressure gauge
Working pressure	2 12 bar
Pressure regulation range	0.5 12 bar
Max. pressure hysteresis	0.25 bar
Standard nominal flow rate	4,000 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:-]
	Inert gases
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Storage temperature	-10 60 °C
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [6:4:4]
Medium temperature	5 60 °C
Ambient temperature	5 60 °C
Product weight	875 g
Mounting type	Optional
	Front panel installation
	Line installation
	with accessories
Pneumatic connection, port 1	NPT1/2-14
Pneumatic connection, port 2	NPT1/2-14
Materials note	Conforms to RoHS
Material control panel	PA
	POM
Material seals	NBR
Material filter	PE
Material housing	Aluminum die cast
Material membrane	NBR
Material bowl	PC
Material separating plate	POM