

Compact cylinder ADN-16-25-I-P-A

Part number: 536230

★ Core product range

FESTO



Data sheet

| Feature | Value |
|--|--|
| Stroke | 25 mm |
| Piston diameter | 16 mm |
| Piston rod thread | M4 |
| Cushioning | P: Flexible cushioning rings/plates at both ends |
| Assembly position | Any |
| Conforms to standard | ISO 21287 |
| Piston-rod end | Female thread |
| Position detection | For proximity sensor |
| Variants | Single-ended piston rod |
| Working pressure | 1 ... 10 bar |
| Mode of operation | double-acting |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Ambient temperature | -20 ... 80 °C |
| Impact energy in end positions | 0.15 J |
| Theoretical force at 6 bar, return stroke | 90 N |
| Theoretical force at 6 bar, advance stroke | 121 N |
| Moving mass with 0 mm stroke | 15 g |
| Additional weight per 10 mm stroke | 14 g |
| Basic weight for 0 mm stroke | 79 g |
| Additional mass factor per 10 mm of stroke | 4 g |
| Mounting type | Optional with through hole with internal (female) thread with accessories |
| Pneumatic connection | M5 |
| Materials note | Conforms to RoHS |
| Material cover | Aluminum Anodized |
| Material seals | TPE-U(PUR) |
| Material piston rod | High alloy steel |
| Material cylinder barrel | Wrought Aluminum alloy Smooth anodized |