

## Datasheet

# RS Pro 4PDT PCB mount Non-Latching Relay, 24V dc Coil, 2 A Non-Latching Relay

RS Stock No: **869-7494**



## Product Details

RS Pro 4PDT non-latching relay has a coil voltage of 24 V dc. The PCB mount relay withstands currents up to 2 A. This relay module is the ideal replacement for the DS4E four-pole small signal relay. It consists of two IM series relays on a 0.8mm FR4 PCB with gold finished pinning to match the original DS4E footprint.

## Features and Benefits

- PCB mount
- No modification required
- Gold plated pins

**Specifications:**

Application	Telecommunications
Coil Voltage	24 V dc
Contact Configuration	4PDT
Contact Material	Gold Plated Palladium-Ruthenium
Depth	10.16 mm
Dimensions	35.56 x 10.16 mm
Length	35.56 mm
Maximum Switching Current (AC)	2 A ac
Maximum Switching Current (DC)	2 A dc
Maximum Switching Power (AC)	62.5 VA
Maximum Switching Power (DC)	60 W
Maximum Switching Voltage (AC)	250 V ac
Maximum Switching Voltage (DC)	220 V dc
Mounting Type	PCB Mount
Number of Poles	4
Relay Switching Classification	Non-Latching Relay
Standards Met	RoHS Compliant
Terminal Type	Plug In