

## Electronic housing - UCS 237-195-H-GD 7035 - 2203344

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Complete housing for PCBs, can be positioned flexibly; includes housing half shells, side panels closed, adhesive domes for PCB attachment, screws for housing and PCB attachment; light gray housing with turquoise-green corner inlays

### Why buy this product

- High degree of application flexibility, thanks to the modular housing design
- Flexible PCB attachment, adapts to virtually all form factors
- Practical customization options
- Reduced logistics outlay, thanks to components which are compatible with one another



### Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4055626404547

### Technical data

#### General

Housing type	Complete housing
Housing material	PC
Color (RAL)	gray (7035)

#### Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 100 °C (depending on power dissipation)

#### Dimensions

Width	237 mm
Height	195 mm
Depth	67 mm

## Electronic housing - UCS 237-195-H-GD 7035 - 2203344

### Technical data

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>