

Shield connection terminal block - SKS 32-D - 3062906

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Shield connection terminal block, for applying the shield directly to the conductive mounting plates

Why buy this product

- The SKS ... spring shield connection clamps are available for cable and conductor diameters of 3 to 20 mm
- According to the requirements of the directive and standards for electrical equipment in potentially explosive areas, as components, shield connections are not able to gain certification. As such, shield connection clamps of type SKS can be used in the Ex area even without appropriate approval and identification.

Key Commercial Data

Packing unit	10 STK
GTIN	 4 046356 562959
GTIN	4046356562959

Technical data

General

Number of levels	1
Number of connections	1
Cable diameter	15 mm ... 32 mm
Color	silver
Open side panel	No

Dimensions

Length	36 mm
Width	32 mm
Height	64 mm

Connection data

Connection method	Spring-cage connection
Conductor cross section solid min.	15 mm ²

Shield connection terminal block - SKS 32-D - 3062906

Technical data

Connection data

Conductor cross section solid max.	32 mm ²
Conductor cross section flexible min.	15 mm ²
Conductor cross section flexible max.	32 mm ²
Conductor cross section AWG min.	6
Conductor cross section AWG max.	3

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>