

# Contact insert - RC-12S2N8D0000 - 1600231

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Contact insert, number of positions: 12, type of contact: Socket, Crimp connection

The figure shows the 6-pos. product version



## Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
GTIN	 4 046356 229203
GTIN	4046356229203

## Technical data

### General

Insertion/withdrawal cycles mechanical	50
Direction of rotation of contact chamber numbering	Counter direction
Coding	N
Contact connection method	Crimp connection
Type of contacts	Socket
Number of positions	12
Contact diameter of power contacts	1 mm
Litz wire cross section of power contacts min.	0.14 mm <sup>2</sup>
Litz wire cross section of power contacts max.	0.56 mm <sup>2</sup>
Nominal current per power contact at 25°C	8 A

### Material

Insulator material	PA66
Contact material	CuZn
Contact surface	Nickel-plated, gold coating

# Contact insert - RC-12S2N8D0000 - 1600231

## Technical data

Specifications according to DIN EN 61984:2001


Nominal / operating voltage of power contacts	150 V
Rated surge voltage of power contacts	1.5 kV
Overvoltage category of power contacts	II
Degree of pollution of power contacts	3
Overvoltage category of signal contacts	II
Degree of pollution of signal contacts	3

## Environmental Product Compliance


REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Drawings


Schematic diagram



Schematic diagram



Schematic diagram



## Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

## Contact insert - RC-12S2N8D0000 - 1600231

### Approvals

EAC



B.01742

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>