





EAN: Part number: Article number: 4013288106988 05074733001 7400 ESD inch Size: Weight: Country of origin: Customs tariff number: 155x37x37 mm 188 g CZ 82054000













- Adjustable Kraftform ESD torque screwdriver with Rapidaptor quick-release chuck
- ESD-safe tool thanks to surface resistance of $<10^9~\rm Ohm$
- Multi-component Kraftform Micro handle for fast and ergonomic screwdriving
- Hexagonal anti-roll feature against rolling away
- Rapidaptor quick-release chuck for bits with 1/4" hex head drive

Wera torque screwdriver. Dependable protection against electrostatic energy and associated damage. Variable torque setting option with highest precision. Simple adjustment of the required torque value without any special tools. Easy-to-read scale value. Rapidaptor quick-release technology for rapid bit change. Unlimited torque to loosen seized screws. Multi-component Kraftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Suitable for bits with 1/4" hexagon head drive as per DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173).

7445 Kraftform ESD adjustable torque screwdrivers with Rapidaptor quick-release chuck, 1/4 inch, 2,5 - 11,5 in. lbs. ESD Series



Adjustable Torque Screwdrivers

Wera ESD Tools

Simple setting

Easy-to-read

Wera's adjustable torque screwdrivers allow variable torque settings with maximum precision and ensure that the user gets the very best results in the familiar Wera design with superior ergonomics.



The requirements for ESD-safe screwdrivers are specified in the European standard DIN EN 61340-5-1. This standard also includes a handle that has to be out of a defined conductive material. The Wera products in the ESD series satisfy these standards and the even more stringent requirements demanded by some technology companies.



Simple setting of the required torque by hand.



Easy-to-read scale value.

Attachable magnifying glass



Articles 7430, 7431 and 7432 all come with a magnifying glass. This can be easily attached on to the scale, dramatically improving visibility.

Further versions in this product family:

Measurement accuracy



Measurement accuracy is \pm 6 % in accordance with the standard DIN EN ISO 6789. Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

(

Versatile



Rapidaptor technology makes the tool adaptable since bits and sockets can be exchanged rapidly.

Unlimited torque



Unlimited torque for loosening seized screws.

			 +++ +++	┝╍╍┝┲╍		
	art. no.	inch	in. lbs.	in. Ibs.	mm	inch
05074733001	7445 ESD	1/4	2.5-11.5	0.5	155	6
05074734001	7446 ESD	1/4	11.0-29.0	1.0	155	6

Web link http://products.wera.de/en/tools_for_the_aerospace_segment_screwdrivers_esd_series_7400_esd_inch.html

Wera - 7400 ESD inch 05074733001 - 4013288106988



Web link http://products.wera.de/en/tools_for_the_aerospace_segment_screwdrivers_esd_series_7400_esd_inch.html

Wera - 7400 ESD inch 05074733001 - 4013288106988