

950 PKL L-key, imperial, BlackLaser, Hex-Plus, 3/16 inch

L-Keys for Hexagon Socket Screws



EAN:	4013288018908	Size:	160x25x5 mm
Part number:	05022076001	Weight:	27 g
Article number:	950 PKL inch	Country of origin:	CZ
		Customs tariff number:	82054000

- L-keys for hexagonal socket screws
- Hex-Plus allows socket head screws to live longer
- Hexagonal ballpoint on the long arm
- BlackLaser for high corrosion protection and long service life
- Metric

High quality L-keys for imperial hexagonal socket screws. Hex-Plus offers a larger contact surface within the screw head. This reduces the notching effects to a minimum and almost completely eliminates the risk of destroying the screw recess. The ball-end on the long arm allows for reliable working even in difficult installation situations. The BlackLaser surface treatment provides outstanding surface protection, even against corrosion, and a long service life. The tools are quickly to hand thanks to the laser-engraved and thereby wear-resistant size markings on the L-keys.

Web link

http://products.wera.de/en/tools_for_the_aerospace_segment_l-keys_l-keys_for_hexagon_socket_screws_950_pkl_inch.html

Wera - 950 PKL inch
05022076001 - 4013288018908

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

L-Keys for Hexagon Socket Screws

L-Keys



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened – and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.

Hex-Plus




Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Ball tip



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, “around-the-corner” screwdriving jobs.

Surface protection



Chrome-plated hexagon L-keys for outstanding surface protection and long service life. High corrosion protection.

Size identification



The size of each L-keys has been engraved by a laser. In addition SPKL L-keys have a colour coding according to sizes – for simple and rapid accessing of the required tool. Making it easy to find the right tool.

Web link






http://products.wera.de/en/tools_for_the_aerospace_segment_l-keys_l-keys_for_hexagon_socket_screws_950_pkl_inch.html

Wera - 950 PKL inch
05022076001 - 4013288018908

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

L-Keys for Hexagon Socket Screws

Further versions in this product family:

					
	inch	mm	mm	inch	inch
05022079001 ¹⁾	0.05	83	14	3 1/4	9/16
05022081001 ¹⁾	1/16	91	15	3 1/2	19/32
05022068001	5/64	100	16	4	5/8
05022070001	3/32	112	18	4 7/16	23/32
05022071001	7/64	119	19	4 3/4	3/4
05022072001	1/8	126	20	5	25/32
05022073001	9/64	132	23	5 3/16	29/32
05022074001	5/32	140	25	5 1/2	1
05022076001	3/16	160	25	6 5/16	1
05022078001	7/32	180	27	7 1/16	1 1/16
05022080001	1/4	190	34	7 1/2	1 5/16
05022082001	5/16	200	36	8	1 7/16
05022095001	3/8	212	38	8 3/8	1 1/2
05022096001	1/2	224	40	9	1 9/16

1) Regular hexagon

Web link

http://products.wera.de/en/tools_for_the_aerospace_segment_l-keys_l-keys_for_hexagon_socket_screws_950_pkl_inch.html

Wera - 950 PKL inch
05022076001 - 4013288018908

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de