

Data Surge Protector SPD CPX Indoor 10/100 Base-T Ethernet RJ45 GDT, TBU CE Compliant, UL 497A

1000-1268

CPX 10/100BT Module (Fused)



Features

- EN/IEC 60950-1, Class I/Div II, ATEX
- UL 497A
- Purpose Designed Modules for all Common Data Protocols

Applications

- 10/100 Base-T Ethernet Networks
- Telecommunications Base Stations
- WISP/ISP
- · IT & Data Centers

- RJ-45 Connectivity
- Fused and Non-Fused Options
- Mount into CPX Chassis 16-Port 1101-972 or 4-Port 1101-1137
- · Point-to-Point Links
- · Control Lines and Sense Loops
- Oil & Gas

Description

Data surge protector (also known as SPD or lightning protector) 1000-1268 from Transtector is an indoor style SPD that utilizes state of the art TBU/GDT technology to protect critical equipment in 10/100 Base-T Ethernet protocol data networks while remaining transparent to data throughput. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by absorbing high amounts of transient energy while maintaining a very low clamping voltage. Transfector Data Signal surge protectors are available in stock with same day shipping.

Electrical Specifications

Minimum	Typical	Maximum	Units
	RJ45		
	Cat5/5e UTP		
	10/100 Base-T Ethernet		
		100	Mb/s
		9	Ohms
		3	pF
	5	11	Vdc
	Minimum	RJ45 Cat5/5e UTP 10/100 Base-T Ethernet	RJ45 Cat5/5e UTP 10/100 Base-T Ethernet 100 9 3

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		GDT, TBU		

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD CPX Indoor 10/100 Base-T Ethernet RJ45 GDT, TBU CE Compliant, UL 497A 1000-1268



Data Surge Protector SPD CPX Indoor 10/100 Base-T Ethernet RJ45 GDT, TBU CE Compliant, UL 497A

1000-1268 CPX 10/100BT Module (Fused)



Protected Pins	[1,2], [3,6]		
Protection Modes	L-G, L-L		
10/1000μs Surge Current			
L-G		100	Α
8/20μs Surge Current			
L-G		20	kA
Response Time		75	ns

Mechanical Specifications

Size

Height	0.99 in	[25.15 mm]
Width	1.63 in	[41.4 mm]
Depth	3.08 in	[78.23 mm]
Weight	0.1 lbs	[45.36 g]

Environmental Specifications

Operating Temperature -40 to +75 deg C Storage Temperature -40 to +75 deg C

Mount Type Protection Module Bay
Installation Hardware 4-20 x 3/8" Plastite Screws

Compliance Certifications

CE Compliant Yes
UL Compliant Yes
Certifications UL 497A
EN/IEC 60950-1

Class 1 Division 2 Groups A,B,C,D T6 Class 1 Zone 2 AEx ec nC IIC T6 Gc

Ex ec nC IIC T6 Gc II 3 G Ex ec nC IIC T6 Gc ITS14ATEX48147X ETL14CA101699377X

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD CPX Indoor 10/100 Base-T Ethernet RJ45 GDT, TBU CE Compliant, UL 497A 1000-1268



Data Surge Protector SPD CPX Indoor 10/100 Base-T Ethernet RJ45 GDT, TBU CE Compliant, UL 497A

1000-1268 CPX 10/100BT Module (Fused)



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Data Surge Protector SPD CPX Indoor 10/100 Base-T Ethernet RJ45 GDT, TBU CE Compliant, UL 497A 1000-1268

URL: https://www.transtector.com/data-surge-protector-spd-cpx-indoor-10-1000-1268-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

1000-1268 CAD Drawing

