

PNOZ m B0

772100



Configurable safe small controllers PNOZmulti 2, base unit, expandable, 20 safe digital inputs, 4 safe semiconductor outputs.


Technical details

General data	
Approval:	CE, UKCA, cULus Listed, KOSHA, TÜV, EAC (Eurasian)
Application range:	Failsafe
Technical data	
Electrical data	
Purpose of U1:	System supply
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Purpose of U2:	Supply of SC outputs
Supply voltage 2 (V):	24 - 24 V
Type of supply voltage U2:	DC
Potential isolation U2:	Yes
Permitted loads:	Resistive, Inductive, Capacitive
Configurable inputs/outputs	
Number of configurable I/Os:	8
Potential isolation of IO:	No
Short circ. prot. n/safe S/C O:	Yes
Voltage at 1 n/safe S/C O:	UB - 2 V at 0.1 A
Inputs	
U input to EN 61131-2 Type 1:	24 V DC

Potential isolation input:	No
Semiconductor outputs	
Potential isolation of S/C O:	Yes
S/C output short circuit proof:	Yes
Test clock outputs	
Number of test pulse outputs:	4
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	0 - 60 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-30, EN 60068-2-78
Condensation permitted?:	Not permitted
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61131-2
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	II
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Potential separation	
Potential isolation 1 between:	SC output and system voltage
Type of potential isolation 1:	Basic insulation
Mechanical data	
Mounting position:	horizontal on top hat rail
DIN-rail dimensions:	35 x 7.5 EN 50022
Housing material lower section:	PC
Housing material front plate:	PC
Housing material upper part:	PC

Connection terminal:	Spring-loaded terminal, Screw terminal
Terminal style:	plug-in
Flex. cond. c/s AWG info:	24 - 12 AWG
Height dimension:	101.4 mm
Width dimension:	45 mm
Depth dimension:	120 mm
Net weight:	235 g
Gross weight:	250 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	7a, 7c I
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead, Lead oxide
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1, 1317-36-8
WEEE klassifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27242207
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC000236

Obligatory accessories



773010B

Basic Licence for PNOZmulti Config.



779211

Chipcard 1 piece 32kB



779201

PNOZmulti Chipcard 1 piece 8kb



751008

PNOZ s Set1spring loaded terminals 45mm



750008

PNOZ s Set1screw terminals 45mm

Optional accessories

773010S

Time lim Licence 2Mth for PNOZmulti Conf

773010Q

Time lim Licence 4Mth for PNOZmulti Conf










779200

PNOZmulti Chipcard Set 10 piece 8KB



779212

PNOZmulti Chipcard Set 10 pieces 32kB

	779261	PNOZ mm0.xp terminator left (10 pcs.)
	779250	PNOZmulti Seal 12 pieces
	779240	PNOZmulti Chipcard Holder (Sparepart)
	779230	PNOZ Chip Card Reader
	773011W	Project Upgr Licence for PNOZmulti Serv
	773010W	Project Upgr Licence f. PNOZmulti Config
	312993	PSSu A USB-CAB05
	773011U	Basic Upgr Licence for PNOZmulti Service
	312992	PSSu A USB-CAB03




773010U

Basic Upgr Licence for PNOZmulti Config


779260

PNOZ mm0.xp connector left (10 pcs)




773011V

User Upgr Licence for PNOZmulti Service




773011B

Basic Licence for PNOZmulti Service



773011K

User Licence for PNOZmulti Service



773010K

User Licence for PNOZmulti Config

773011G

Project Licence for PNOZmulti Service
